

ISE Electronics Corp. Japan (Noritake/Itron)

CU200211-MCPB-S31A

2x20, 5x7 CharSet, Punkt + Komma, 11 x 8 mm Zeichengröße

Modulgröße: 273 x 76 mm

Connector CN1 (links), 3 polig

Pin	Belegung	Info
1	Vcc	5 V, rund 1 A
2	Serial In	TTL Level
3	Gnd	

Connector CN2 (rechts), 26 polig

Pin	Belegung	Info	Pin	Belegung	Info
1	? D0		14	Gnd	
2	Gnd		15	? D7	
3	? D1		16	Gnd	
4	Gnd		17	?	
5	? D2		18	Gnd	
6	Gnd		19	?	
7	? D3		20	Gnd	
8	Gnd		21	?	
9	? D4		22	Gnd	
10	Gnd		23	?	
11	? D5		24	Gnd	
12	Gnd		25	?	
13	? D6		26	?	

Jumper

J6	J5	J4	J3	J2	J1	J0	Funktion	
X	X	X	X	X	X	0	Display Test	
X	X	X	X	X	X	1	normal Operation	
X	X	X	X	X	0	X	???	
X	X	X	X	X	1	X		?
X	X	X	1	1	X	X	Parity Selection	
X	X	X	1	0	X	X		Even Parity
X	X	X	0	X	X	X		Odd Parity
X	X	X	0	X	X	X	None Parity	
1	1	1	X	X	X	X	Baud Rate Selection	
1	1	0	X	X	X	X		19200 BPS
1	0	1	X	X	X	X		9600 BPS
1	0	0	X	X	X	X		4800 BPS
0	1	1	X	X	X	X		2400 BPS
0	1	0	X	X	X	X		1200 BPS
0	1	0	X	X	X	X	600 BPS	
1	1	1	1	1	1	1	Factory Setting	

0: Short 1: Open X: Don't Care