


Vishay TSOP 1738, Vishay TSOP 1838, Vishay TSOP 11xx series, Siemens SFH 5110, Radio Shack 276-0137, Mitsumi IR Preamp KEY-COOSV (0924G), Toshiba TK19 444 TFMS 5360, Temic TFMS 5380 by Telefunken Semiconductors, Sharp IS1U60, Everlight IRM-8601S, Sony SBX 1620-12, Sharp GP1U271R
 Optional: OK1 if the PowerOn function is used to start/shutdown the host PC
 Optional: J1 if a bootloader will be used: [BootloadHID](#)
 If the bootloader get be used be sure to write the right fuse bits. Otherwise the bootloader will be deleted after the first flashing.

Fuse Bits	
0 <input checked="" type="checkbox"/> SPIEN	BODLEVEL [7] <input type="text" value="1"/>
1 <input type="checkbox"/> RSTDISBL	BOOTSZ [10:9] <input type="text" value="00"/>
0 <input checked="" type="checkbox"/> EESAVE	CKSEL [3:0] <input type="text" value="1111"/>
0 <input checked="" type="checkbox"/> CKDPT	SUT [5:4] <input type="text" value="10"/>
1 <input type="checkbox"/> WDTON	
0 <input checked="" type="checkbox"/> BODEN	
0 <input checked="" type="checkbox"/> BOOOTRST	

Lock Bits	
1 <input type="checkbox"/> Boot Lock Bit 01	1 <input type="checkbox"/> Lock Bit 1
1 <input type="checkbox"/> Boot Lock Bit 02	1 <input type="checkbox"/> Lock Bit 2
1 <input type="checkbox"/> Boot Lock Bit 11	
1 <input type="checkbox"/> Boot Lock Bit 12	

Also take look to the file *Makefile* of the project *bootloadHID*.

Picture of an assembled USB IR Remote Receiver device



AVR Source description

To compile the source [Atmel AVR Studio](#) and [WinAVR](#) will be needed.

irmpconfig.h:

(pin can be changed if the IR receiver diode is not connected to PD4)

```
#define IRMP_PORT PORTB
#define IRMP_DDR DDRD
#define IRMP_PIN PIND
#define IRMP_BIT 4 // use PD4 as IR input
```

configUSBIRRemoteReceiver.h:

```
//enter here the Irmp build date:
const char IrmpVersion[] = "16.04.2010";
#define USE_PowerOnFunction /* unkomen if you don't want to use the PowerOn function */

#ifdef USE_PowerOnFunction
#define SWITCH_PORT PORTC /* PORTx - register for Switch output */
#define SWITCH_BIT PC5 /* bit where OK1 will be connected */
#define SWITCH_DDR DDRC /* Switch data direction register */
#endif
```

Screen shot settings/option dialog



Device Connected: If the device got connected to the host the icon will change to green and the included Irmp build date will be shown.

PowerOn Function Status: If the PowerOn function is enabled the icon will be green. Use the button to enable/disable the PowerOn function. If the option "Disable PowerOn when initialized"

is checked the PowerOn function will be automatically disabled when the plugin get's initialized. So the IR code what is used for PowerOn can be used on the host

for a different function.

Received IR Code: Will show the last received IR code

Trained IR Code: Will show the IR code what got stored in EEPROM for PowerOn

Manage Trained IR Code:

Read Trained IR Code: Reads the IR code stored in EEPROM

Clear Trained IR Code: Will clear the actual stored IR code in EEPROM. The next received IR code will be stored as new PowerOn IR code.

IR Polling Time: For different IR receiver diodes it is possible to adjust the polling time. A usefull time is between 66 - 100µs

Minimum of Repeats: The device will debounce the remote control. With the minimum of repeats the number of needed repeats can be adjusted until the same IR code getting sent again to the host.

A repeat of 0 means no change to the remote control.

USB_IR_Remote_Receiver.ini

[IRMP Protocols]

List of supported protocols of the device (depend on IRMP version).

If a new protocol is added to the device the DLL doesn't need to be updated. Just add the new protocol in this section:

name_of_protocol=IRMP_ID

[Settings]

Default the device is opened delayed with 2000ms. This value can be changed when adding:

StartUpDelay=desired_value_in_milliseconds

{Default 2000}

Default there is no key suppression. The received IR codes are getting forwarded as they are getting decoded and received ba the DLL.

If the host software isn't fast enough to handle fast repeating IR codes a timer for key suppression can be used.

This option disallow a received IR to get sent to the host software if a previous received IR code got sent and the key suppression is still active.

Key Suppression=desired_value_in_milliseconds


{Default 0}

Add this value to enable a log memo in the settings dialog:

Debug=1

{Default 0}

USB IR Remote Receiver device installation on Windows 7 x86, just plug in the device. The driver will be installed automatically



USB IR Remote Receiver device installation on Windows XP SP3, just plug in the device. The driver will be installed automatically



Function prototypes in "USB IR Remote Receiver.dll" library:

The DLL will handle the communication between the HID AVR device and the host.


The USB IR Remote Receiver DLL can be used directly with DVBViewer in the 'Plugins' directory as input plugin.

The USB IR Remote Receiver DLL can be also used directly with Girder in the 'Plugins' directory. Tested with Girder 3.2.9 (last Freeware version), 4.0.5.2 and 5.0.10.



Also it can be used for other programs to handle the device with the functions InitNative or InitPAnsiChar.

Screen shots from the demo sources

Example output with the DLL_Demo.exe (source Delphi 2010):



Example output with the DLL_Demo_Console.exe (source Visual Studio 2008):



Delphi:

```
function Version():PAnsiChar; stdcall external USBIRRemoteReceiver name 'Version';
function Copyright():PAnsiChar; stdcall external USBIRRemoteReceiver name 'Copyright';
function PluginName():PAnsiChar; stdcall external USBIRRemoteReceiver name 'PluginName';
procedure ShowSettings(Handle : THandle); stdcall external USBIRRemoteReceiver name 'ShowSettings';

function InitNative(Callback : TCallbackNativeIRData):boolean; stdcall external USBIRRemoteReceiver name 'InitNative';
function InitPAnsiChar(Callback : TCallbackPAnsiChar):boolean; stdcall external USBIRRemoteReceiver name 'InitPAnsiChar';
```

```
type
  TCallbackNativeIRData = procedure(IRCode : TIRData); stdcall;
```

```
type
  TCallbackPAnsiChar = procedure(Protocol, Address, Command, Flags : PAnsiChar); stdcall;
```

```
type
  TIRData = packed record
    Protocol : byte;
    Address : word;
    Command : word;
    Flags : byte;
  end;
```

C++ Builder / Microsoft Visual C++:

```
#define USBIRRemoteReceiver "USB_IR_Remote_Receiver.dll";
```

```

const char * __stdcall Version();
const char * __stdcall Copyright();
const char * __stdcall PluginName();
void __stdcall ShowSettings( HWND Handle );

BOOL __stdcall InitNative( CallbackNativeIRData * Callback );
BOOL __stdcall InitPAnsiChar( CallbackPAnsiChar * Callback );

typedef void ( __stdcall * CallbackNativeIRData ) ( IRMP_DATA IRCode );
typedef void ( __stdcall * CallbackPAnsiChar ) ( char * Protocol, char * Address, char * Command, char * Flags );

typedef struct
{
    byte Protocol;
    word Address;
    word Command;
    byte Flags;
} IRMP_DATA;

```

function **Version()**:PAnsiChar; stdcall external *USBIRRemoteReceiver* name 'Version';

Function will return the plugin version as PAnsiChar.

Parameters

none

Return values

Function will return USB IR Remote Receiver DLL version as PAnsiChar.

function **Copyright()**:PAnsiChar; stdcall external *USBIRRemoteReceiver* name 'Copyright';

Function to get copyright of USB IR Remote Receiver DLL.

Parameters

none

Return values

Function will return copyright as PAnsiChar.

function **PluginName()**:PAnsiChar; stdcall external *USBIRRemoteReceiver* name 'PluginName';

Function to get USB IR Remote Receiver DLL plugin name.

Parameters

none

Return values

Function will return USB IR Remote Receiver DLL plugin name as PAnsiChar.

procedure **ShowSettings(Handle : THandle)**; stdcall external *USBIRRemoteReceiver* name 'ShowSettings';

Procedure to show options/settings dialog of USB IR Remote Receiver DLL.

Parameters

Handle

[in] Window handle of the calling program. The dialog will be shown modal.

Notes:

The options/settings dialog will only be shown if the DLL got initialized first by *InitNative* / *InitPAnsiChar*.

function **InitNative(Callback : TCallbackNativeIRData):boolean**; stdcall external *USBIRRemoteReceiver* name 'InitNative';

Function to init USB IR Remote Receiver for native callback.

Parameters

Callback

[in] Procedure pointer of a procedure of type struct [TCallbackNativeIRData](#).

Return values

If the function succeeds, the return value is *True*.

If the function fails, the return value is *False*.

Notes:

The device get only open if the *Callback* procedure pointer isn't *NIL* / *NULL*.

For closing the device, unloading/disable the plugin call this function again with *Callback* = *NIL* / *NULL*.

The defined Callback procedure will receive the IR codes like the type struct [TIRData](#).

function **InitPAnsiChar(Callback : TCallbackPAnsiChar):boolean**; stdcall external *USBIRRemoteReceiver* name 'InitPAnsiChar';

Function to init USB IR Remote Receiver for native callback.

Parameters

Callback

[in] Procedure pointer of a procedure of type struct [TCallbackPAnsiChar](#).

Return values

If the function succeeds, the return value is *True*.

If the function fails, the return value is *False*.

Notes:

The device get only open if the *Callback* procedure pointer isn't *NIL / NULL*.

For closing the device, unloading/disable the plugin call this function again with *Callback = NIL / NULL*.

The defined Callback procedure will receive the IR codes as *Protocol*, *Adress*, *Command* and *Flags* : **PAnsiChar**.

For more information see also the demo application.

Copyright © 2010 Portisch.