

Item	Series	Model	Capacity (mAh)	Thickness(mm)	Width(mm)	Length (mm)	Approx weight (g)	Internal resistance (mΩ)	Voltage(V)	Tab width	Width between tabs
1	1226	501226	100	5.0±0.2	11.2±0.8	25.2±0.8	1,9	280↓	3,7	2	保证两极耳绝缘胶不重合
2	1230	501230	120	5.0±0.2	12.0±0.8	30.0±0.8	2,9	240↓	3,7	2	保证两极耳绝缘胶不重合
3		401230	100	4.0(+0.1 -0.2)	12.0±0.5	30.0±0.8	2	180↓	3,7	2	4.0-8.0
4	1235	401235	125	4.0±0.2	11.5±0.8	35.0±0.8	2,8	200↓	3,7	2	保证两极耳绝缘胶不重合
5		431235	130	4.2(+0.1 -0.3)	12.0±0.5	35.0±0.5	2,9	200↓	3,7	2	两极耳绝缘胶不重叠、不超出电芯宽度
6		451235	130	4.3±0.2	11.5±0.8	34.5±0.8	3,5	140↓	3,7	2	两极耳绝缘胶不重叠中心距 5.0±1
7		501235	140	5.0(+0 -0.4)	12.0±0.8	34.0±0.8	3,8	150↓	3,7	2	两极耳绝缘胶不重叠合
8		601235	170	6.0±0.2	12.0±0.8	35.0±0.8	4,2	150↓	3,7	2	两极耳绝缘胶不重叠、不超出电芯宽度
9		601235L	160	5.8±0.2	12.0±0.8	34.5±0.8	4,1	200↓	3,7	2	两极耳中心距不重叠
10	1245	601245	250	6.0±0.2	11.5±0.5	45.0±0.5	5,4	120↓	3,7	2	两极耳绝缘胶不重叠、不超出电芯宽度
11	1430	401430	100	3.9(+0.1 -0.2)	13.5±0.8	29.5±0.8	2,4	180↓	3,7	2	6.0±1
12		401430H	120	4.0±0.2	13.5±0.8	29.5±0.8	2,4	180↓	3,7	2	两极耳绝缘胶不重叠、不超出电芯宽度
13		451430	135	4.5±0.2	14.0±0.8	30.0±0.8	3	200↓	3,7	2	两极耳中心距不超出电芯宽度、绝缘胶不重叠
14		501430	155	5.0±0.2	13.5±0.8	29.5±0.8	3	150↓	3,7	2	两极耳中心距不重叠，不超出电芯宽度。
15		551430	170	5.3±0.2	14.0±0.8	30.0±0.8	3,2	180↓	3,7	2	两极耳中心距不重叠，不超出电芯宽度。
16	1630	301630	100	3.0±0.2	15.0±0.8	29.0±0.8	2,3	220↓	3,7	2	保证极耳绝缘胶不重合

17		401730	170	4.2(+0.05 -0.2)	16.8±0.8	29.5±0.8	3,7	180↓	3,7	2	6.5±0.8
18		501730	190	4.8±0.2	17.0±0.8	30.0±0.8	4	120↓	3,7	2	6.0±0.8
19		601730	220	5.8±0.2	17.0±0.8	29.7±0.8	5	150↓	3,7	2	5.5±0.8
20	1745	401745	250	4.0(+0.10 -0.20)	16.8±0.8	44.8±0.8	5,6	120↓	3,7	2	6.5±0.8
21		501745	320	5.0±0.2	16.5±0.8	45.0±0.8	6,7	75↓	3,7	3	两极耳绝缘胶不重叠
22		601745	400	6.0±0.2	17.0±0.5	45.0±0.8	7,8	100↓	3,7	3	两极耳绝缘胶不重叠，不超出电芯宽度。
23	1840	301840	170	2.9±0.2	17.0±0.8	39.2±0.8	4	150↓	3,7	2	7.0±0.8
24	2025	402025	135	4.0(+0.1 -0.3)	20.0±0.8	25.0±0.8	3,2	150↓	3,7	3	8.0±0.8
25		422025	140	4.1±0.2	19.5±0.8	24.5±0.8	3,4	200↓	3,7	3	8.0±0.8
26		512025	180	5.1(+0.0 -0.4)	20.0±0.8	25.0±0.8	3,9	180↓	3,7	2	8.5±0.8
27		622025	225	6.0±0.2	20.0±0.8	25.0±0.8	4,6	150↓	3,7	2	7.2±0.8
28		622025L	220	5.9±0.2	20.0±0.8	25.0±0.8	5,1	150↓	3,7	2	7.2±0.8
29		382030L	170	3.6±0.2	20.0±0.8	30.0±0.8	4,7	150↓	3,7	3	8.0±0.8
30		382030	180	3.8(+0.1 -0.3)	19.8±0.8	29.8±0.8	4,8	150↓	3,7	3	8.0±0.8
31		402030	190	4.0(+0.1 -0.2)	19.8±0.8	29.8±0.8	4	150↓	3,7	3	8.0±0.8
32		402030P	180	4.3±0.2	20.0±0.8	30.0±0.8	4	120↓	3,7	4	8.5±0.8
33		482030	230	4.8±0.2	19.8±0.8	29.8±0.8	5	110↓	3,7	3	8.0±0.8

34		502030	240	5.0(+0.1 -0.2)	20.0±0.8	30.0±0.8	5,9	110↓	3,7	3	8.0±0.8
35		582030	300	<u>5.8±0.2</u>	20.0±0.8	30.0±0.8	5	130↓	3,7	3	8.0±0.8
36		582030L	270	5.7±0.2	20.0±0.8	30.0±0.8	5	150↓	3,7	3	7.0±0.8
37		582030LN	270	5.7±0.2	20.0±0.8	30.0±0.8	5	150↓	3,7	3	7.0±0.8
38		552035	330	5.5(+0.15 -0.25)	20.0±0.8	34.8±0.8	6,5	120↓	3,7	3	7.0±0.8
39	2035	702035	400	7.0(+0 -0.4)	20.0±0.8	35.0±0.8	7,8	100↓	3,7	2	6.0±0.8
40		402035	230	4.0(+0.1 -0.2)	19.8±0.8	34.5±0.8	4,95	150↓	3,7	3	8.0±0.8
41		402035N	230	4.0(+0.1 -0.2)	20.0±0.8	34.5±0.8	4,95	150↓	3,7	3	8.0±0.8
42		502035	300	5.0(+0.1 -0.2)	20.0±0.8	35.0±0.8	6,1	120↓	3,7	3	7.5±0.8
43		582035	340	5.8±0.2	20.0±0.5	34.5±0.5	6,8	80↓	3,7	3	7.5±0.8
44	2040	402040	250	3.8±0.2	19.2±0.8	40.0±0.8	5,1	120↓	3,7	3	25.0±0.8
45		402040P	230	3.8±0.2	20.0±0.8	40.0±0.8	5,1	150↓	3,7	3	8.0±0.5
46	2040	402040H	280	3.9±0.2	19.2±0.8	39.0±0.8	6,3	120↓	3,7	3	7.5±0.8
47		422040	270	4.0±0.2	19.2±0.8	40.0±0.8	5,1	150↓	3,7	3	8.8±0.8
48		502040	320	4.8±0.2	19.0±0.8	39.0±0.8	6,7	120↓	3,7	2	8.0±0.8
49	2045	452045	340	4.3±0.2	20.0±0.8	44.0±0.8	6,4	80↓	3,7	3	7.5±0.8
50		562045N	450	5.4±0.2	20.0±0.8	44.0±0.8	9,7	80↓	3,7	3	7.0±0.8

51	2040	562045	450	5.4±0.2	20.0±0.8	44.0±0.8	9,7	80↓	3,7	3	7.0±0.8
52		602045	500	6.0±0.2	20.0±0.8	45.0±0.8	10,5	90↓	3,7	3	7.5±0.8
53	2239	382239	275	3.8±0.2	22.0±0.8	39.0±0.8	6,1	120↓	3,7	3	9.5±0.8
54		402239	300	4.0±0.2	22.0±0.8	38.0±0.8	6,6	100↓	3,7	3	10.0±0.8
55		482239	350	4.8(+0.1 -0.2)	20.8±0.8	38.0(+0.8 -0.8)	7,3	140↓	3,7	3	8.5±0.8
56	2239	402248	350	4.0±0.2	22.0±0.8	47.8±0.8	8	85↓	3,7	3	10.0±0.8
57		452248	400	4.3±0.2	22.0±0.8	48.0±0.8	7,5	80↓	3,7	3	10.0±0.8
58		502248	470	4.9±0.2	20.8±0.8	47.5±0.8	10	75↓	3,7	3	9.0±0.8
59		702248	650	6.9±0.2	21.5±0.8	48.0±0.8	13,2	70↓	3,7	3	7.0±0.8
60		602248	560	5.8±0.2	20.8±0.8	48.0±0.8	12,5	80↓	3,7	3	7.0±0.8
61	2439	402439	320	3.8±0.2	24.0±0.8	39.0±0.8	6,8	110↓	3,7	3	10.0±0.8
62		502439	400	5.0(+0.05 -0.2)	23.8±0.8	38.8±0.8	8,4	100↓	3,7	3	10.5±0.8
63		562439	460	5.6(+0 -0.4)	24.0±0.8	39.0±0.8	9,2	80↓	3,7	3	10.8±0.8
64		602439	500	6.0(+0.1 -0.2)	24.0±0.8	39.0±0.8	10,2	80↓	3,7	3	10.5±0.8
65	2533	502533	370	5.0(+0.1 -0.3)	25.0±0.8	33.0±0.8	7,5	120↓	3,7	3	10.0±0.8
66		572533	400	5.5±0.2	25.0±0.8	33.0±0.8	8	100↓	3,7	3	10.5±0.8
67		402533	260	4.0±0.2	25.0±0.8	32.0±0.8	5,7	120↓	3,7	3	11.5±0.8

68		452533	300	4.3±0.2	24.7±0.8	33.0±0.8	6,6	100↓	3,7	<u>3</u>	11.5±0.8
69	2730	372730L	165	2.8±0.2	26.5±0.8	30.0±0.8	4	150↓	3,7	3	14.5±0.8
70		302730	170	3.0±0.2	26.5±0.8	30.0±0.8	4,2	150↓	3,7	3	14.5±0.8
71		362730	245	3.6±0.2	27.0±0.8	30.0±0.8	5,1	100↓	3,7	3	11.5±0.8
72		382730	260	3.8(+0.1 -0.2)	27.0±0.8	30.0±0.8	5,4	100↓	3,7	3	13.5±0.8
73		452730	310	4.5±0.20	27.0±0.8	30.0±0.8	6,5	130↓	3,7	3	13.5±0.8
74		282730	150	2.6±0.20	26.2±0.8	29.2±0.8	3,8	170↓	3,7	2	15.0±0.8
75	2845	452845H	530	4.3±0.2	28.0±0.8	45.0±0.8	10,5	80↓	3,7	3	11.5±0.8
76		752845	810	7.0±0.2	27.7±0.8	44.0±0.8	16	65↓	3,7	3	10.0±0.8
77	2933	402933	320	4.0(+0.1 -0.2)	28.5±0.8	32.5±0.8	6,9	100↓	3,7	3	13.0±0.8
78		302933	210	2.8±0.2	29.4±0.8	33.0±0.8	4,8	150↓	3,7	3	15.0±0.8
79		403040	430	4.0±0.2	30.0±0.8	40.0±0.8	9	75↓	3,7	3	15.0±0.8
80		423040	450	4.2±0.2	29.5±0.8	40.0±0.8	9,4	80↓	3,7	3	13.5±0.8
81		453040	490	4.5(+0.0 -0.4)	30.0±0.8	40.0±0.8	10,3	80↓	3,7	3	13.0±0.8
82		503040	570	5.0±0.2	29.5±0.8	40.2±0.8	11,5	65↓	3,7	3	13.0±0.8
83		343048	430	3.2±0.2	29.2±0.8	47.2±0.8	9,1	70↓	3,7	3	13.0±0.8
84		403048	600	4.2(+0.05 -0.3)	29.8±0.8	47.8±0.8	12,4	80↓	3,7	3	15.0±0.8

85		503048	720	5.0±0.2	30.0±0.8	48.0±0.8	14,2	65↓	3,7	3	13.0±0.8
86		523048	760	5.2±0.2	30.0±0.8	48.0±0.8	15	65↓	3,7	3	13.0±0.8
87		583048	800	5.8(+0 -0.2)	30.0±0.5	48.0±0.5	15,8	50↓	3,7	3	13.0±0.8
88		603048L	850	6.0(+0 -0.4)	30.0±0.8	48.0±0.8	16,6	60↓	3,7	3	12.5±0.8
89		603048	900	6.0±0.2	30.0±0.8	48.0±0.8	17,1	60↓	3,7	3	12.5±0.8
90		703048	1000	7.0±0.2	30.0±0.5	48.0±0.5	19,5	50↓	3,7	3	11.5±0.8
91		803048	1100	8.0±0.2	30.0±0.8	48.0±0.8	21,9	60↓	3,7	3	13.2±0.8
92	3350	383350	630	3.8(+0.05 -0.3)	32.7±0.8	50.0±0.8	12,8	65↓	3,7	3	20.8±0.8
93		233350	310	2.2±0.2	33.0±0.8	49±0.8	7	100↓	3,7	3	17.5±0.8
94	3436	503436	600	5.1±0.2	34.0±0.8	36.0±0.8	10,6	80↓	3,7	3	14.5±0.8
95		283436	300	2.6±0.2	33.5±0.5	35.2±0.8	6,3	120↓	3,7	3	20.3±0.8
96		403436	450	4.0±0.2	34.0±0.8	35.0±0.8	9,8	90↓	3,7	3	18.0±0.8
97		603436	630	5.8±0.2	33.5±0.8	35.5±0.8	12,8	60↓	3,7	3	16.0±0.8
98	3442	293442	380	2.9±0.2	34.0±0.8	42.0±0.8	8,5	100↓	3,7	3	16.0±0.8
99		403442	550	4.0(+0.15 -0.2)	34.0±0.8	42.0±0.8	11,2	70↓	3,7	3	17.5±0.8
100		443442	600	4.2±0.2	34.0±0.8	42.0±0.8	12	80↓	3,7	3	17.0±0.8
101		553442	720	5.5(+0.05 -0.3)	34.0±0.8	42.0±0.8	15,9	60↓	3,7	3	17.0±0.8

102		613442	800	6.0±0.2	33.5(+0.5 -0.8)	41.5±0.8	17,7	50↓	3,7	3	16.0±0.8
103		523448	850	5.4(+0 -0.4)	34.0±0.8	48.0±0.8	17	60↓	3,7	4	18.0±0.8
104		523448N	820	5.2±0.2	34.0±0.8	48.0±0.8	17	70↓	3,7	4	18.0±0.8
105		603448	950	5.85±0.2	33.5±0.8	48.0±0.8	18,9	50↓	3,7	4	16.0±0.8
106		783448L	1250	7.8±0.2	33.8±0.8	48.0±0.8	24,6	50↓	3,7	4	16.0±0.8
107		783448	1300	7.8(+0.2 -0.3)	33.8±0.8	48.0±0.8	24,5	50↓	3,7	4	16.0±0.8
108		753448N	1200	7.5±0.2	34.0±0.8	48.0±0.8	24,5	60↓	3,7	4	16.0±0.8
109		783448N	1300	8.1±0.2	34.0±0.8	48.0±0.8	24,5	50↓	3,7	4	16.0±0.8
110		293450	500	2.9±0.2	34.0±0.8	50.0±0.8	10,7	80↓	3,7	3	16.5±0.8
111	3450	293450N	460	2.9±0.2	34.0±0.8	50.0±0.8	10,7	80↓	3,7	3	16.5±0.8
112		323450H	550	<u>3.0±0.25</u>	34.2±0.8	<u>50.2±0.8</u>	11,3	65↓	3,7	3	16.5±0.8
113		383450	650	3.8(+0.05 -0.3)	34.0±0.5	50.0±0.5	12	50↓	3,7	3	17.5 (+1 -0.5)
114		383450H	700	3.8(+0.05 -0.2)	33.8±0.8	50.2±0.8	14,5	60↓	3,7	3	17.5 (+1 -0.5)
115		403450	680	4.0(+0.05 -0.2)	33.8±0.8	49.8±0.8	14,2	60↓	3,7	3	17.5±0.8
116		433450	750	4.3(+0.05 -0.2)	34.0±0.5	50.0±0.5	15,3	60↓	3,7	3	17.0±0.8
117		483450	820	4.6±0.2	34.0±0.8	50.0±0.8	16,3	60↓	3,7	4	15.5±0.8
118		483450G	820	4.6±0.2	34.0±0.8	50.0±0.8	16,8	60↓	3,7	4	15.5±0.8

119		523450	900	5.2±0.2	34.0±0.8	50.0±0.8	17,7	65↓	3,7	3	18.0±0.8
120		603450	1000	5.8±0.2	33.5±0.8	49.5±0.8	19,5	60↓	3,7	4	16.5±0.8
121		723450	1300	7.2(+0.25 -0.2)	34.0±0.8	50.0±0.8	24	60↓	3,7	4	16.0±0.8
122		753450	1300	7.5(+0.1 -0.2)	33.8±0.8	49.8±0.8	24	50↓	3,7	4	16.0±0.8
123		783450N	1300	7.7±0.2	34.0±0.8	50.0±0.8	24	60↓	3,7	4	16.0±0.8
124		603450	1000	5.8±0.2	33.5±0.8	49.5±0.8	19,5	60↓	3,7	4	16.5±0.8
125		423450G	750	4.2±0.2	34.0±0.8	50.0±0.8	14,8	65↓	3,7	3	17.5±0.8
126		293455	520	2.8±0.2	33.0±0.8	55.0±0.8	10,9	70↓	3,7	3	16.5±0.8
127		293455H	550	3.1(+0 -0.4)	34.0±0.8	54.5±0.8	11,3	70↓	3,7	3	16.5±0.8
128		553455	1100	5.5±0.2	34.0±0.8	55.0±0.8	21,5	55↓	3,7	4	17.0±0.8
129		393455	700	3.8±0.2	33.8±0.8	55.0±0.8	14,7	50↓	3,7	3	14.5±0.8
130		423455	780	4.2(+0.1 -0.2)	33.8±0.8	55.0±0.8	15,2	50↓	3,7	3	14.5±0.8
131		523455	1050	5.2(+0.1 -0.2)	33.8±0.8	55.0±0.8	19,6	50↓	3,7	4	17.0±0.8
132		623455	1250	6.2(+0.05 -0.2)	33.2±0.8	54.5±0.8	24,3	45↓	3,7	4	16.5±0.8
133	3458	483458	1000	4.8±0.2	34.0±0.8	58.0±0.8	19,3	60↓	3,7	4	17.0±0.8
134		503458	1000	5.0(+0.05 -0.25)	33.5±0.8	57.8±0.8	19,8	45↓	3,7	4	17.0±0.8
135		523458	1050	5.2(+0.05 -0.2)	33.5±0.8	57.8±0.8	21,6	45↓	3,7	4	18.5±0.8

136	3562	363562	730	3.5(+0.1 -0.4)	34.0±0.8	60.8±0.8	14,9	50↓	3,7	3	18.5±0.8
137		363562M	730	3.5(+0.1 -0.4)	34.0±0.8	60.8±0.8	15,2	50↓	3,7	3	19.0±0.5
138		383562	850	3.8(+0.05 -0.2)	34.5±0.8	61.5±0.8	16,5	65↓	3,7	3	16.0±0.8
139		423562	950	4.2±0.2	34.5±0.8	61.5±0.8	19	55↓	3,7	4	18.5±0.8
140		503562	1200	5.0±0.2	35.0±0.8	62.0±0.8	22,5	50↓	3,7	4	17.5±0.8
141	3650	883650T	1620	8.6±0.2	35.5±0.8	49.5±0.5	33,3	50↓	3,7	4	16.0±0.8
142		883650	1650	8.8±0.2	35.5±0.8	50.0±0.8	34	50↓	3,7	4	16.0±0.8
143		703650	1200	7.0±0.2	36.0±0.8	50.0±0.8	24,5	50↓	3,7	4	16.0±0.8
144		753650	1260	7.3(+0.2 -0.25)	36.0±0.5	50.0±0.8	26	60↓	3,7	4	16.0±0.8
145		453759	1020	4.5(+0 -0.4)	37.0±0.8	59.0±0.8	20,3	50↓	3,7	3	17.0±0.8
146		453759N	1020	4.5(+0.3 -0.2)	37.0±0.8	59.0±0.8	21	55↓	3,7	3	17.0±0.8
147		503759	1100	4.8±0.2	37.0±0.8	59.0±0.8	19	55↓	3,7	4	18.0±0.8
148		503759N	1100	5.0±0.2	37.0(+0.5 -0.8)	59.0±0.8	19	55↓	3,7	4	18.0±0.8
149		503759H	1200	4.9±0.2	37.0±0.8	59.0±0.8	24,3	60↓	3,7	4	18.0±0.8
150		503759LN	1050	4.8±0.2	37.0±0.8	59.0±0.8	21,7	55↓	3,7	4	18.0±0.8
151		533759	1250	5.2±0.2	37.0±0.8	59.0(+0.5 -0.8)	25,1	60↓	3,7	4	20.0±0.8
152		563759	1300	5.6(+0.1 -0.2)	36.5±0.8	59.0±0.8	24,7	50↓	3,7	4	17.5±0.8

153		583759	1350	5.8(+0.05 -0.2)	36.5±0.8	59.0±0.8	24,7	50↓	3,7	4	17.0±0.8
154		633759	1400	6.1±0.2	36.0±0.8	59.0±0.8	26,3	50↓	3,7	4	18.5±0.8
155		633759N	1400	6.1±0.2	36.0±0.8	59.0±0.8	28,5	50↓	3,7	4	18.5±0.8
156		563759N	1200	5.5±0.2	36.5±0.8	59.0±0.8	24,6	50↓	3,7	4	17.5±0.8
157		373759	850	3.7±0.2	37.0±0.8	59.0±0.8	16,8	65↓	3,7	4	19.0±0.8
158		373759G	850	3.7±0.2	37.0±0.8	59.0±0.8	16,8	65↓	3,7	4	19.0±0.8
159		373759L	820	3.6±0.2	37.0±0.8	59.0±0.8	16,8	65↓	3,7	4	19.0±0.8
160		303759	650	2.9±0.2	37.0±0.8	59.0±0.8	13,3	65↓	3,7	3	18.5±0.8
161	3944	343944	530	3.4±0.2	39.0±0.8	44.0±0.8	11,5	80↓	3,7	3	10.0±0.8
162		383944N	580	3.8±0.2	39.0±0.8	44.0±0.8	12	100↓	3,7	3	10.0±0.8
163		383944	580	3.6±0.2	39.0±0.8	44.0±0.8	11,96	100↓	3,7	3	10.0±0.8
164	4169	384169	1100	3.8(+0.15 -0.2)	40.8±0.8	69.0±0.8	22	50↓	3,7	4	23.0±0.8
165		474169	1400	4.6(+0.15 -0.2)	40.8±0.8	68.8±0.8	27,5	45↓	3,7	4	22.5±0.8
166		634169	2000	6.3±0.2	40.8±0.8	69.0±0.8	37,2	50↓	3,7	4	20.5±0.8
167		634169D	2000	6.3±0.2	40.8±0.8	69.0±0.8	37,2	50↓	3,7	4	20.5±0.8
168		804169	2650	8.0±0.2	40.8±0.8	68.8±0.8	46	50↓	3,7	4	22.0±0.8
169		454261	1050	4.5(+0 -0.4)	40.8±0.8	60.0±0.8	21	60↓	3,7	3	17.5±0.8

170	4261	454261N	1050	4.3±0.2	40.8±0.8	60.0±0.8	21,5	60 ↓	3,7	3	17.5±0.5
171		474261	1200	4.5±0.2	40.8±0.8	60.0±0.8	23,4	50 ↓	3,7	3	17.5±0.8
172		724261	2000	7.0(+0.3 -0.2)	42.0±0.8	60.8±0.8	37,5	50 ↓	3,7	4	20.5±0.8
173		474261M	1200	4.5±0.2	41.2±0.8	60.0±0.8	23,5	50 ↓	3,7	4	27.0±0.8
174	4261	694261	1800	6.7±0.2	42.0±0.8	60.8±0.8	35,2	50 ↓	3,7	4	22.5±0.8
175	4296	604296	2800	6.0(+0.1 -0.25)	41.8±0.5	96.0±0.5	51,2	50 ↓	3,7	4	22.5±0.8
176		654296	2900	6.4(+0.15 -0.2)	41.8±0.8	96.0±0.8	53,2	50 ↓	3,7	4	17.0±0.8
177		504452	1150	4.8±0.2	44.0±0.8	52.0±0.8	22,3	60 ↓	3,7	4	20.8±0.8
178	45135	4045135	3000	4.1±0.2	44.5±0.8	133.5±0.8	61	40 ↓	3,7	4	23.0±0.8
179		5045135	3600	5.0±0.2	44.5±0.8	133.5±0.8	74	50 ↓	3,7	4	22.0±0.8
180		6345135	4500	<u>6.3±0.2</u>	45.0±0.8	133.5±0.8	98	50 ↓	3,7	4	18.0±0.8
181	48135	4048135	2900	4.0(+0 -0.4)	48.0(+0.0 -0.5)	135(+0.0 -0.5)	59	50 ↓	3,7	4	
182	5055	435055	1100	4.3(+0 -0.4)	49.5±0.8	55.0±0.8	24	60 ↓	3,7	4	28.0±0.8
183		565055	1600	5.6±0.2	49.0±0.8	55.0±0.8	31,8	50 ↓	3,7	4	24.5±0.8
184		605055	1500	5.8±0.2	49.0±0.8	55.0±0.8	31,8	50 ↓	3,7	4	24.5±0.8
185	5058	515058	1500	4.9±0.2	49.2±0.8	58.0±0.8	30,2	60 ↓	3,7	4	30.8±0.8
186		515058N	1500	4.9±0.2	49.2±0.8	58.0±0.8	30,2	60 ↓	3,7	4	30.8±0.8

187	5060	385060	1100	3.8(+0.1 -0.2)	49.0±0.8	59.0±0.8	22,5	80 ↓	3,7	4	28.0±0.8
188		525068	1800	5.0±0.2	50.0±0.8	68.0±0.8	34,7	50 ↓	3,7	4	24.5±0.8
189		555068	2000	5.4±0.2	50.0±0.8	68.0±0.8	38,6	50 ↓	3,7	4	25.3±0.8
190	5085	325085	1300	3.0(+0.25 -0.2)	50.0±0.8	85.0±0.8	26	55 ↓	3,7	4	26.0±0.8
191		385085	1700	3.8(+0.05 -0.2)	49.8±0.8	84.5±0.8	32,5	50 ↓	3,7	4	26.0±0.8
192		425085	1900	4.2(+0.05 -0.2)	49.8±0.8	84.0±0.8	36,2	50 ↓	3,7	4	28.0±0.8
193		655085	3000	6.4±0.2	48.8±0.8	84.0±0.8	55,9	40 ↓	3,7	4	24.0±0.8
194		655085N	3000	6.5±0.2	49.2±0.8	84.2±0.8	55,5	50 ↓	3,7	4	24.0±0.8
195		855085	4100	8.5±0.2	50.0±0.8	85.0±0.8	74	40 ↓	3,7	4	24.0±0.8
196		755085	3600	7.5±0.2	49.5±0.8	84.5±0.8	72,1	50 ↓	3,7	4	24.0±0.8
197		855085N	4100	8.5±0.2	50.0±0.8	85.0±0.8	74	40 ↓	3,7	4	24.0±0.8
198	5152	505152	1300	4.8±0.2	50.8(+0.5 -0.8)	52.0(+0.5 -0.8)	25,8	60 ↓	3,7	4	28.0±0.8
199		505152N	1300	4.8±0.2	50.8(+0.5 -0.8)	52.0(+0.5 -0.8)	26,38	50 ↓	3,7	4	28.0±0.8
200		555152	1500	5.3±0.2	50.8±0.8	52.0±0.8	30,5	55 ↓	3,7	4	28.0±0.8
201	5165	365165	1100	3.6(+0 -0.04)	50.8±0.8	65.0±0.8	23,7	60 ↓	3,7	4	27.0±0.8
202		385165	1300	3.9(+0.05 -0.2)	50.8±0.8	65.0±0.8	26,2	50 ↓	3,7	4	27.0±0.8
203		505165	1750	5.0±0.2	50.5±0.8	65.0±0.8	34,2	45 ↓	3,7	4	28.0±0.8

204	5100	505165LN	1600	4.8±0.2	50.5±0.8	65.0±0.8	33	50 ↓	3,7	4	28.0±0.8
205		555165	2000	5.5±0.2	50.8±0.8	64.8±0.8	38,2	60 ↓	3,7	4	28.0±0.8
206		555165L	1850	5.2±0.2	50.0±0.8	65.0±0.8	38,2	60 ↓	3,7	4	28.0±0.8
207	5280	405280	1900	4.0±0.2	52.0±0.8	77.5±0.8	36,9	45 ↓	3,7	4	28.5 (+0.5 -1.5)
208		505280	2200	4.9±0.2	52.0±0.8	77.5±0.8	44,4	45 ↓	3,7	4	24.0±0.8
209	5460	455460	1500	4.5±0.2	54.0±0.8	60.0±0.8	29,2	50 ↓	3,7	4	28.5±0.8
210		455460N	1400	4.3±0.2	53.7±0.8	59.7±0.8	28,6	60 ↓	3,7	4	28.5±0.8
211		585460	2000	5.7±0.2	53.5±0.8	59.7±0.8	37	50 ↓	3,7	4	28.0±0.8
212	5555	465555	1400	4.6±0.2	55.0±0.8	55.0±0.8	28	60 ↓	3,7	4	28.5±0.8
213	5585	355585	1600	3.2±0.2	55.0±0.8	84.5±0.8	32,5	40 ↓	3,7	4	29.05±0.8
214		425585	2100	4.1±0.2	54.5±0.8	84.5±0.8	40,8	40 ↓	3,7	4	27.3±0.8
215	5899	375899	2200	3.5±0.2	57.8±0.8	98.0±0.8	42,8	50 ↓	3,7	4	34.5±0.8
216	58110	5558110	4100	5.5±0.3	58.0±0.8	110.0±0.8	76,5	50 ↓	3,7	4	32.0±0.8
217	6066	506066	2000	4.8±0.2	60.0±0.8	65.0±0.8	38	60 ↓	3,7	4	34.5±0.8
218		606066	2400	5.9±0.2	60.0±0.8	65.0±0.8	46	50 ↓	3,7	4	34.5±0.8
219		466066	1900	4.6±0.2	60.0±0.8	65.0±0.8	36,3	50 ↓	3,7	4	34.5±0.8
220	6580	456580	2600	4.5±0.2	64.0±0.8	78.5±0.8	50	40 ↓	3,7	4	32.5±0.8

221	3562	476580	2750	4.7±0.2	63.5±0.8	78.5±0.8	52	40↓	3,7	4	18.0±0.8
222	3562	553562P	1300	5.7±0.2	34.8±0.8	61.8±0.8	26,8	50↓	3,7	6	31.5±0.8
223		383562P	800	3.8(+0.05 -0.2)	35.0±0.5	61.5±0.5	16,8	50↓	3,7	6	17.2±0.8

There are some letters beside the model No. N stands for Ternary Material, H stands for high discharge type, L stands for lower capacity, T stands for very flat cell, P stands for big discharge current cell, G stands for high temperature cell, D stands for low temperature cell, M stands for space between tabs.

此型号表上的型号中，表中电池后缀N代表三元体系；电池后缀H代表高容量,L代表低容量,T代表厚度薄,P代表大电流电池,G代表高温电池.D代表低温电池，M代表极耳中心距。

电芯型号一览表 Model List

No	Series	Model	Capacity (mAh)		Dimension (mm)			IMP	Nominal Voltage	Weight (Approx)	Tab Pitch	Tab Width	产品类型	模具
					T	W	L						常规	
			Typ.	Min.	Max.	Max.	Max.	< mohm	v	g	mm	mm		
2	**1230	381230	80	80	3,8	12,8	30,5	250	3,7	2,3	5	2	√	√
3		451230	100	100	4,6	12,5	30,5	200	3,7	2,7	5	2	√	√
4		501230	130	130	5,2	12,5	30,5	200	3,7	3,0	5	2	√	√
5		601230	145	145	6,2	12,5	30,5	200	3,7	3,5	5	2	√	√
7	**1244	341244	128	128	3,4	12,5	44,5	200	3,7	1,7	5	2	√	√
8	**1430	401430	120	120	4,2	14,5	30,8	200	3,7	3,0	5	2	√	√
9		501430	170	160	5,2	14,5	30,5	200	3,7	3,5	5	2	√	√
10		521430	170	170	5,4	14,5	30,5	200	3,7	3,8	5	2	√	√
11		601430	190	190	6,2	14,2	30,5	200	3,7	4,1	5	2	√	√
12		651430	220	220	7,0	14,5	32,5	180	3,7	4,6	5	2	√	√
13	**1730	401730	150	150	4,2	17,5	30,5	200	3,7	3,5	5	2	√	√
14		451730	175	175	4,7	17,5	30,5	200	3,7	4,1	5	2	√	√
15		501730	190	190	5,2	17,5	30,5	200	3,7	4,5	5	2	√	√
16		601730	200	200	6,2	17,5	30,5	180	3,7	5,0	5	2	√	√
17		651730	210	210	6,5	17,5	30,8	180	3,7	5,2	5	2	√	√
18	**2030	322030	150	150	3,4	20,5	30,5	200	3,7	3,5	8	3	√	√
19		402030	180	180	4,2	20,5	30,8	200	3,7	4,2	10	3	√	√
20		502030	270	250	5,0	20,5	30,5	180	3,7	5,5	8	3	√	√
21		552030	270	270	5,7	20,5	30,5	180	3,7	6,2	8	3	√	√
22		582030	290	270	6,1	21,0	31,0	180	3,7	7,0	7,5	3	√	√
23		602030	300	300	6,2	20,5	30,5	120	3,7	7,0	7,5	3	√	√
24	**2034	402034	230	230	4,2	21,0	34,8	180	3,7	5,2	10	3	√	√
25		552034	350	320	5,7	20,5	34,5	120	3,7	7,0	7	3	√	√
26		572034	350	320	6,0	20,5	34,5	120	3,7	7,0	7	3	√	√
27		752034	450	430	7,5	20,5	35,0	120	3,7	9,0	6	5	√	√

28		802034	500	500	8,2	20,5	34,5	90	3,7	10,0	5,5	2	√	√
29	**2040	602040	500	450	6,2	20,5	40,5	120	3,7	9,0	7,5	3	√	√
30	**2459	452459	600	550	4,7	24,5	59,5	90	3,7	12,0	12	3	√	√
31		502459	600	600	5,2	24,5	59,5	60	3,7	13,0	10	5	√	√
32		582459	750	750	6,0	24,5	59,5	60	3,7	15,5	11	3	√	√
33		602459	800	800	6,2	24,5	59,5	60	3,7	16,5	10	3	√	√
34		622459	800	800	6,4	24,5	59,5	60	3,7	15,5	10	3	√	√
35	**3048	353048	470	440	3,7	30,5	48,8	120	3,7	9,0	20	3	√	√
36		363048	500	500	3,8	30,5	48,5	90	3,7	10,5	18	3	√	√
37		453048	600	600	4,5	30,5	48,5	60	3,7	12,5	18	3	√	√
38		503048	710	710	5,2	30,5	48,5	60	3,7	14,5	17	3	√	√
39		623048	900	900	6,4	30,5	48,5	60	3,7	17,0	16	3	√	√
40	**3145	603145	800	800	6,5	31,5	45,5	60	3,7	16,0	17	3	√	√
41		403145	530	530	4,2	31,5	45,5	90	3,7	10,5	19	3	√	√
43	**3265	753265	1750	1750	7,7	32,5	65,5	60	3,7		15	5	√	√
44		383265	820	800	3,8	32,5	65,5	60	3,7	16,5	21	5	√	√
48	**3448	353448	520	520	3,5	34,5	48,5	90	3,7	11,0	18	5	√	√
49		383448	580	580	3,8	34,5	48,5	90	3,7	12,0	18	5	√	√
50		443448	700	700	4,6	34,5	48,5	60	3,7	14,5	22,5		√	√
51		603448	1000	950	6,2	34,5	48,5	60	3,7	19,0	19	3	√	√
52	**3562	383562	850	820	4,0	35,5	62,5	60	3,7	17,0	20	5	√	√
53		453562	1000	900	4,7	35,5	62,5	60	3,7	20,0	21	5	√	√
54		503562	1000	1000	5,2	35,5	62,5	60	3,7		19	5	√	√
55		553562	1250	1150	5,5	35,5	62,5	60	3,7		18	5	√	√
56		623562	1350	1350	6,5	35,5	62,5	60	3,7			5	√	√
57	**3647	643647	1100	1050	6,4	36,5	47,5	60	3,7	21,5	20	3	√	√
59	**3750	403750	750	720	4,2	37,5	50,5	60	3,7	23,0	24	3	√	√
60		433750	850	820	4,5	37,5	51,0	60	3,7	23,0	5		√	√
61	**3759	403759	950	900	4,2	37,5	59,5	60	3,7	18,0	21	5	√	√
62		433759	1000	1000	4,5	37,0	60,0	60	3,7	20,0	20	5	√	√

63		503759	1100	1100	5,2	37,5	59,5	60	3,7		23	5	√	√
64		513759	1200	1200	5,1	37,5	59,5	60	3,7	23,3	20,5	5	√	√
65		553759	1250	1250	5,5	37,5	59,5	60	3,7	25,0	20	5	√	√
66		583759	1400	1400	5,8	37,5	59,5	60	3,7	26,5	21	3	√	√
67		603759	1250	1250	6,2	37,5	59,5	60	3,7				√	√
68		823759	1500	1500	8,4	37,5	59,8	60	3,7	29,5	23	3	√	√
69		634047	1250	1250	6,4	40,5	47,8	60	3,7	23,8	24	5	√	√
70		864047	1600	1600	9,0	40,5	47,8	60	3,7	29,7	26	3	√	√
71	**4070	424070	1250	1200	4,4	40,5	70,5	60	3,7	26,0	25	5	√	√
72		584070	1100	1100	6,0	40,5	47,5	60	3,7		25	5	√	√
77		604451F	800	800	6,2	44,5	51,5	60	3,2		18	3		√
78	**4468	404468	1300	1300	4,2	44,0	70,0	60	3,7		30	5	√	√
80	**4768	354768	1000	1000	3,7	47,5	68,5	60	3,7		32	5	√	√
81		454768	1400	1400	4,7	47,5	68,5	60	3,7	30,0	32	5	√	√
82		504768	1600	1500	5,2	47,5	68,5	60	3,7		32	5	√	√
83		554768	2000	2000	5,9	47,8	68,0	40	3,7	78,0	31	5	√	√
84		604768	2000	2000	6,2	47,5	68,5	40	3,7		31	5	√	√
86	**4850	354850	820	820	3,7	48,5	50,5	60	3,7	16,5	34	5	√	√
87	**4865	654865	2000	2000	6,5	48,5	66,0	40	3,7		21	5	√	√
88		704865	2500	2500	7,2	48,5	65,5	40	3,7	49,0	39	5	√	√
89		754865	2600	2600	7,7	48,5	65,5	40	3,7	49,0	29	5	√	√
90		784865	2800	2800	8,0	48,5	65,5	40	3,7	51,0	40	5	√	√
91	**48135	8048135	6000	6000	8,2	48,5	135,5	20	3,7	110,0	27	5	√	√
92		4048135	2500	2500	4,3	48,5	135,8	40	3,7	53,0	33	5	√	√
93	**48168	8048168	6000	6000	7,0	48,0	168,5	20	3,7		24	10	√	√
94		6248168	6000	6000	6,4	48,5	168,5	20	3,7	111,0	31	5	√	√
95	**5070	385070	1400	1400	4,0	50,5	70,5	60	3,7	27,5	36	5	√	√
96		505070	1800	1800	5,1	50,5	70,5	60	3,7	35,0	34	5	√	√
97		525070	2000	2000	5,5	50,5	70,5	40	3,7	38,0	34	5	√	√
98		555070	2000	2000	5,5	50,5	70,5	40	3,7	38,0	34	5	√	√

99		605070	2200	2200	6,2	50,5	70,5	40	3,7	43,0	33	5	√	√
100		705070	2400	2400	7,0	50,5	70,5	40	3,7	48,0	32	5	√	√
101		725070	2800	2800	7,5	50,5	70,5	40	3,7		32	5	√	√
102		755070	2600	2600	7,5	49,5	70,0	40	3,7	48,0	32	5	√	√
103		805070	3000	3000	8,2	50,5	70,5	30	3,7	57,0	32	5	√	√
104	**5076	585076	2400	2400	6,0	50,5	76,5	40	3,7		34	5	√	√
105	**5085	405085	1600	1600	4,2	50,5	85,5	60	3,7	41,0	32	5	√	√
106		455085	2100	2100	4,7	50,5	85,5	40	3,7	41,0	35	5	√	√
107		475085	2000	2000	4,5	50,3	85,5	40	3,7	41,0	33	5	√	√
108		605085	2800	2800	6,2	50,5	85,5	40	3,7		33	5	√	√
109		755085	3600	3600	7,7	50,5	85,5	30	3,7	67,0	32	5	√	√
110		805085	4000	4000	8,2	50,5	85,5	30	3,7	74,0	33	5	√	√
111	**50158	5050158	4500	4500	5	50,5	158,5	30	3,7	86,0	34	5	√	√
112	**5163	405163	1300	1300	4,2	51,5	63,5	60	3,7		35	5	√	√
113	**5165	385165	1300	1300	4,0	51,5	65,5	60	3,7		37	5	√	√
114		525165	1800	1800	5,4	51,5	65,5	60	3,7	35,0	35	5	√	√
115	**5267	425267	1600	1600	4,4	52,5	67,5	60	3,7	31,0	37	5	√	√
116		435267	1600	1600	4,35	52,5	67,8	60	3,7	32,5	37	5	√	√
117	**55125	4255125	3250	3250	4,6	55,5	125,5	30	3,7	66,5	40	5	√	√
118	**58117	4558117	3200	3200	4,7	58,5	118,0	30	3,7		42	5	√	√
119		6558117	5000	5000	6,5	58,0	120,0	30	3,7		40	5	√	√
120	**58150	5558150	5200	5200	5,5	58,5	150,5	30	3,7		41,5	5	√	√
121		6058150	5700	5700	6,2	58,5	150,5	30	3,7		41	5	√	√
122	**5990	455990	2700	2700	4,7	60,0	90,8	40	3,7	51,0	43	5	√	√
123	**6193	656193	4000	4000	6,5	61,5	93,5	30	3,7	76,0	43	5	√	√
124	**61113	6461113	5000	5000	6,45	61,0	112,0	30	3,7	94,5	42	5	√	√
125	**63203	5563203	8000	8000	5,5	64,0	203,5	20	3,7	152,0	42	5	√	√
126		6263203	10000	10000	6,4	65,0	204,0	20	3,7	189,0	41	10	√	√
127		6463203	10000	10000	6,4	64,0	203,5	20	3,7	184,0	41	10	√	√
128	**63226	9263226	9500	9500	9,4	63,0	226,0	20	3,2	235,0	20	10	√	√

129	**6495	306495	1850	1850	3,1	64,5	95,5	60	3,7	79,0	46	5	√	√
130		626495	4200	4200	6,2	64,5	94,5	30	3,7		46	6	√	√
131	**6572	506572	2500	2500	5	65,5	72,5	40	3,7		50	5	√	√
132		556572	2750	2750	5,7	65,5	72,8	40	3,7	53,0	48,5	5	√	√
133	**67123	4067123	4000	4000	4,2	67,5	123,5	30	3,7		52	5	√	√
134		5067123	4800	4800	5,2	67,5	123,0	30	3,7	134,0	51	5	√	√
135	**73105	5073105	4800	4800	5,3	73,0	105,5	30	3,7		55	5	√	√
136		6273105	5000	5000	6,4	73,5	105,5	30	3,7	95,0	57	5	√	√
137	**74145	5574145	7200	7200	5,7	74,0	145,0	20	3,7	134,0	57	5	√	√
138	**7590	557590	4000	4000	5,5	75,5	90,5	30	3,7	77,0	58	5	√	√
139	**75123	5075123	5000	5000	5,2	73,5	123,5	30	3,7	99,0	59	5	√	√
140	**78230	9078230F	12000	12000	9,2	79,0	232,0	15	3,2		38	20		√
141	**82140	3882140	5000	5000	3,8	85,0	140,0	30	3,7		66	5	√	
142	**86110	5586110H	4000	4000	5,5	86,5	120,0	10	3,7			50		√
143	**88127	5088127	7200	7200	5,2	89,0	127,5	20	3,7		67	5	√	

Model	Voltage	Capacity	Internal resistance	Discharge rate
ICR07300	3.7V	≥100	≤300	Normal
ICR08240	3.7V	≥80	≤300	
ICR08350	3.7V	≥120	≤250	
ICR08400	3.7V	≥150	≤250	
ICR10160	3.7V	≥80	≤300	
ICR10180	3.7V	≥100	≤200	
ICR10220	3.7V	≥130	≤200	
ICR10250	3.7V	≥150	≤200	
ICR10300J	3.7V	≥220	≤150	
ICR10430	3.7V	≥320	≤150	
ICR10440	3.7V	≥360	≤150	
ICR12250	3.7V	≥200	≤200	
ICR12300	3.7V	≥280	≤150	
ICR13490	3.7V	≥600	≤100	
ICR14250	3.7V	≥250	≤150	
ICR14430	3.7V	≥600	≤80	
	3.7V	≥650	≤80	
ICR14500	3.7V	≥700	≤80	
	3.7V	≥750	≤80	
ICR14630	3.7V	≥900	≤80	
ICR14650	3.7V	≥1050	≤80	
ICR15226	3.7V	≥350	≤150	
ICR16340	3.7V	≥600	≤80	
	3.7V	≥650	≤80	
ICR17280	3.7V	≥500	≤120	
ICR17305	3.7V	≥550	≤120	
ICR17335	3.7V	≥650	≤120	
ICR17360	3.7V	≥700	≤80	

ICR17500	3.7V	≥ 1100	≤ 80	
	3.7V	≥ 1200	≤ 80	
ICR17650	3.7V	≥ 1550	≤ 80	
ICR17670	3.7V	≥ 1600	≤ 80	
ICR18490	3.7V	≥ 1300	≤ 80	
	3.7V	≥ 1350	≤ 80	
	3.7V	≥ 1400	≤ 80	
ICR18580	3.7V	≥ 1800	≤ 80	
18650	3.7V	2000	≤ 80	
18650	3.7V	2200	≤ 80	
18650	3.7V	2300	≤ 80	
18650	3.7V	2400	≤ 80	
18650	3.7V	2600	≤ 80	
18650	3.6V	1300	≤ 80	3-5C
18650	3.6V	1300	≤ 80	10C
18650	3.6V	1300	≤ 80	15C