




Specifications CA3085, CA3085A, CA3085B

Absolute Maximum Ratings

Supply Voltage	+7.0V
Unregulated Input Voltage	
CA3085	30V
CA3085A	40V
CA3085B	50V
Storage Temperature Range	-65°C to +150°C
Junction Temperature	+175°C
Plastic DIP Package	+150°C
Lead Temperature (Soldering 10s)	+265°C

Thermal Information

Thermal Resistance	θ_{JA}	θ_{JC}
Metal Can (Without Heat Sink)	156°C/W	68°C/W
Plastic DIP Package	155°C/W	-
Maximum Package Power Dissipation		
Plastic DIP (Without Heat Sink)		
Up to $T_A = 55^\circ\text{C}$	630mW	
Above $T_A = 55^\circ\text{C}$	Derate Linearly at 6.67mW/°C	
Metal Can (With Heat Sink)		
Up to $T_C = 55^\circ\text{C}$	1.6W	
Above $T_C = 55^\circ\text{C}$	Derate Linearly at 16.7mW/°C	

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

Operating Conditions

Operating Voltage Range	+1.7V to +46V	Operating Temperature Range	-55°C to +125°C
-------------------------	---------------	-----------------------------	-----------------

Maximum Voltage Ratings

The following chart gives the range of voltages which can be applied to the terminal listed vertically with respect to the terminals listed horizontally. For example, the voltage range between vertical Terminal Number 7 and horizontal Terminal Number 1 is +3 to -10V.

TERMINAL NUMBER	5	6	7	8	1	2	3	4
5	-	+5 -5	Note 1	Note 1	Note 1	Note 1	Note 1	+10 0
6	-	-	Note 1	Note 1	Note 1	Note 1	Note 1	Note 1
7	-	-	-	+3 -10	-103	Note 1	Note 1	+ (Note 2) 0
8	-	-	-	-	+5 -1	Note 1	Note 1	Note 1
1	-	-	-	-	-	+10 - (Note 2)	0 - (Note 2)	+ (Note 2) 0
2	-	-	-	-	-	-	0 -	+ (Note 2) 0
3	-	-	-	-	-	-	-	+ (Note 2) 0
4	-	-	-	-	-	-	-	Substrate and Case

NOTES:

1. Voltages are not normally applied between these terminals; however, voltages appearing between these terminals are safe, if the specified voltage limits between all other terminals are not exceeded.
2. 30V (CA3085); 40V (CA3085A); 50V (CA3085B)

Maximum Current Ratings

TERMINAL NUMBER	I_{IN} (mA)	I_{OUT} (mA)
5	10	1.0
6	1.0	-0.1
7	1.0	-0.1
8	0.1	10
1	20	150
2	150	60
3	150	60
4	-	-

Specifications CA3085, CA3085A, CA3085B

DC Electrical Specifications $T_A = +25^{\circ}\text{C}$, Unless Otherwise Specified

PARAMETERS	SYMBOL	TEST CONDITIONS		CA3085			CA3085A			CA3085B			UNITS
				MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
DC CHARACTERISTICS													
Reference Voltage	V _{REF}	V ⁺ _{IN} = 15V (Figure 3)		1.4	1.6	1.8	1.5	1.6	1.7	.15	1.6	1.7	V
Quiescent Regulator Current	I _{quiescent}	V ⁺ _{IN} = 30V (Figure 3)		-	3.3	4.5	-	-	-	-	-	-	mA
		V ⁺ _{IN} = 40V (Figure 3)		-	-	-	-	3.65	5	-	-	-	mA
		V ⁺ _{IN} = 50V (Figure 3)		-	-	-	-	-	-	-	4.05	7	mA
Input Voltage Range	V _{IN(range)}			7.5	-	30	7.5	-	40	7.5	-	50	V
Maximum Output Voltage	V _{O(MAX)}	V ⁺ _{IN} = 30, 40, 50V (Note 1); R _L = 365Ω; Term. No. 6 to GND (Figure 3)		26	27	-	36	37	-	46	47	-	V
Maximum Output Voltage	V _{O(MIN)}	V ⁺ _{IN} = 30V (Figure 3)		-	1.6	1.8	-	1.6	1.7	-	1.6	1.7	V
Input - Output Voltage Differential	V _{IN} -V _{OUT}			4	-	28	4	-	38	3.5	-	48	V
Limiting Current	I _{LIM}	V ⁺ _{IN} = 16V, V ⁺ _{OUT} = 10V, R _{SCP} = 6Ω (Note 2) (Figure 6)		-	96	120	-	96	120	-	96	120	mA
Load Regulation (Note 3)		I _L = 1 to 100mA, R _{SCP} = 0		-	-	-	-	0.025	0.15	-	0.025	0.15	%V _{OUT}
		I _L = 1 to 100mA, R _{SCP} = 0, T _A = 0°C to +70°C		-	-	-	-	0.035	0.6	-	0.035	0.6	%V _{OUT}
		I _L = 1 to 12mA, R _{SCP} = 0		-	0.003	0.1	-	-	-	-	-	-	%V _{OUT}
Line Regulation (Note 4)		I _L = 1mA, R _{SCP} = 0		-	0.025	0.1	-	0.025	0.075	-	0.025	0.04	%/V
		I _L = 1mA, R _{SCP} = 0, T _A = 0°C to +70°C		-	0.04	0.15	-	0.04	0.1	-	0.04	0.08	%/V
Equivalent Noise Output Voltage	V _{NOISE}	V ⁺ _{IN} = 25V (Figure 10)	C _{REF} = 0	-	0.5	-	-	0.5	-	-	0.5	-	mVp-p
			C _{REF} = 0.22μF	-	0.3	-	-	0.3	-	-	0.3	-	mVp-p
Ripple Rejection		V ⁺ _{IN} = 25V, f = 1kHz (Figure 11)	C _{REF} = 0	-	50	-	-	50	-	45	50	-	dB
			C _{REF} = 2μF	-	56	-	-	56	-	50	56	-	dB
Output Resistance	r _O	V ⁺ _{IN} = 25V, f = 1kHz (Figure 11)		-	0.075	1.1	-	0.075	0.3	-	0.075	0.3	Ω
Temperature Coefficient of Reference and Output Voltages	V _{REF} , V _O (Note 4)	I _L = 0, V _{REF} = 1.6V		-	0.0035	-	-	0.0035	-	-	0.0035	-	%/°C


Specifications CA3085, CA3085A, CA3085B

DC Electrical Specifications $T_A = +25^\circ\text{C}$, Unless Otherwise Specified (Continued)

PARAMETERS	SYMBOL	TEST CONDITIONS	CA3085			CA3085A			CA3085B			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
LOAD TRANSIENT RECOVERY TIME												
Turn On	t _{ON}	V ⁺ _{IN} = 25V, +50mA Step (Figure 16)	-	1	-	-	1	-	-	1	-	μs
Turn Off	t _{OFF}	V ⁺ _{IN} = 25V, -50mA Step (Figure 16)	-	3	-	-	3	-	-	3	-	μs
LOAD TRANSIENT RECOVERY TIME												
Turn On	t _{ON}	V ⁺ _{IN} = 25V, f = 1kHz, 2V Step	-	0.8	-	-	0.8	-	-	0.8	-	μs
Turn Off	t _{OFF}		-	0.4	-	-	0.4	-	-	0.4	-	μs


NOTES:

- 30V (CA3085), 40V (CA3085A), 50V (CA3085B)
- R_{SCP} : Short Circuit Protection Resistance
- Load Regulation = $[\Delta V_{OUT} \div V_{OUT}(\text{initial})] \times 100\%$
- Line Regulation = $[\Delta V_{OUT} \div V_{OUT}(\text{initial})(\Delta V_{IN})] \times 100\%$



All Resistance Values are in Ohms


FIGURE 1. SCHEMATIC DIAGRAM OF CA3085 SERIES



$V_{OUT} = 3.5\text{V to } 20\text{V}$ (0 to 90mA)
 Regulation = 0.2% (Line and Load)
 Ripple < 0.5mV at Full Load

FIGURE 2. APPLICATION OF THE CA3085 SERIES IN A TYPICAL POWER SUPPLY

Test Circuits and Typical Performance Curves



TEST	R_L	V_{IN}	CONNECT TERM NO. 6	S
V_{REF}	∞	+1.6	Open	Open
$I_{QUIESCENT}$	∞	+40	Open	Open
$V_{OUT(MAX)}$	365 Ω	+40	Ground	Closed
$V_{OUT(MIN)}$	10k	+30	Terminal No.1	Open

FIGURE 3. TEST CIRCUIT FOR V_{REF} , $I_{QUIESCENT}$, $V_{OUT(MAX)}$, $V_{OUT(MIN)}$




FIGURE 4. $I_{QUIESCENT}$ vs V_{+IN}





FIGURE 5. NORMALIZED $I_{QUIESCENT}$ vs T_A



- NOTES:
- $V_{OUT} = 1.6 \times (R_1 + R_2 \div R_1)$
 - The limits current is inversely proportional to R_{SCP}

FIGURE 6. TEST CIRCUIT FOR LIMITING CURRENT




FIGURE 7. I_{LIM} vs T_A




FIGURE 8. LOAD REGULATION CHARACTERISTICS

Test Circuits and Typical Performance Curves (Continued)




FIGURE 9. LINE REGULATION TEMPERATURE CHARACTERISTICS




FIGURE 10. TEST CIRCUIT FOR NOISE VOLTAGE




FIGURE 11. TEST CIRCUIT FOR RIPPLE REJECTION AND OUTPUT RESISTANCE

TEST PROCEDURES FOR TEST CIRCUIT FOR RIPPLE REJECTION AND OUTPUT RESISTANCE

Output Resistance

Conditions

1. $V_{IN} = +25V$, $C_{REF} = 0$, Short E_1
2. Set E_{S2} at 1kHz so that $E_2 = 4V_{RMS}$
3. Read V_{OUT} on a VTVM, such as a Hewlett-Packard, HP400D or Equivalent
4. Calculate R_{OUT} from $R_{OUT} = V_{OUT}(R_L/E_2)$

Ripple Rejection - I

Conditions

1. $V_{IN} = +25V$, $C_{REF} = 0$, Short E_2
2. Set E_{S1} at 1kHz so that $E_1 = 3V_{RMS}$
3. Read V_{OUT} on a VTVM, such as a Hewlett-Packard, HP400D or Equivalent
4. Calculate Ripple Rejection from $20 \log (E_1/V_{OUT})$

Ripple Rejection - II

Conditions

1. Repeat Ripple Rejection I with $C_{REF} = 2\mu F$




FIGURE 12. r_O vs f




FIGURE 13. NORMALIZED r_O vs T_A

Test Circuits and Typical Performance Curves (Continued)




FIGURE 14. TEMPERATURE COEFFICIENT OF V_{REF} AND V_{OUT}




FIGURE 15. DISSIPATION LIMITATION ($V_{IN} - V_{OUT}$ vs I_{OUT})





FIGURE 16. TURN-ON AND TURN-OFF RECOVERY TIME TEST CIRCUIT WITH ASSOCIATED WAVEFORMS

See Application Note AN6157 for further information

Typical Regulator Circuits




FIGURE 17. TYPICAL HIGH CURRENT VOLTAGE REGULATOR CIRCUIT





FIGURE 18. TYPICAL CURRENT REGULATOR CIRCUIT



All Resistance Values are in Ohms
 D_1 : 1N4001 or Equivalent
 Q_1 : 2N5322 or Equivalent

NOTE:

1. $R_1 = 0.7 I_L (\text{Max})$

FIGURE 19. TYPICAL SWITCHING REGULATOR CIRCUIT




FIGURE 20. COMBINATION POSITIVE AND NEGATIVE VOLTAGE REGULATOR CIRCUIT