

```
1-gdb-set confirm off
1^done
(gdb)
2-gdb-set width 0
2^done
(gdb)
3-gdb-set height 0
3^done
(gdb)
4-interpreter-exec console echo
4^done
(gdb)
5-gdb-show prompt
5^done,value="(gdb) "
(gdb)
6-gdb-set new-console on
&"No symbol table is loaded. Use the \"file\" command.\n"
6^error,msg="No symbol table is loaded. Use the \"file\" command."
(gdb)
7 target remote localhost:4242
No symbol table is loaded. Use the "file" command.
target remote localhost:4242
&"target remote localhost:4242\n"
localhost:4242: Es konnte keine Verbindung hergestellt werden, da der Zielcomputer die Verbindung
verweigerte.
&"localhost:4242: Es konnte keine Verbindung hergestellt werden, da der Zielcomputer die Verbindung verweigerte.\n"
7^error,msg="localhost:4242: Es konnte keine Verbindung hergestellt werden, da der Zielcomputer die Verbindung
verweigerte."
(gdb)
8 load D:\\Users\\Kucky.ADMIN-PC\\Entwicklung\\Eclipse\\workspace\\BotTwo\\Debug\\BotTwo.elf
&"load D:\\\\Users\\\\Kucky.ADMIN-PC\\\\Entwicklung\\\\Eclipse\\\\workspace\\\\BotTwo\\\\Debug\\\\BotTwo.elf \n"
load D:\\Users\\Kucky.ADMIN-PC\\Entwicklung\\Eclipse\\workspace\\BotTwo\\Debug\\BotTwo.elf
You can't do that when your target is `None'
&"You can't do that when your target is `None'\n"
8^error,msg="You can't do that when your target is `None'"
(gdb)
```

```
9-environment-directory D:/Users/Kucky.ADMIN-PC/Entwicklung/Eclipse/workspace/BotTwo D:/Users/Kucky.ADMIN-PC/Entwicklung/Eclipse/workspace/BotTwo/.settings D:/Users/Kucky.ADMIN-PC/Entwicklung/Eclipse/workspace/BotTwo/Debug D:/Users/Kucky.ADMIN-PC/Entwicklung/Eclipse/workspace/BotTwo/Release
9^done,source-path="D:/Users/Kucky.ADMIN-PC/Entwicklung/Eclipse/workspace/BotTwo;D:/Users/Kucky.ADMIN-PC/Entwicklung/Eclipse/workspace/BotTwo/.settings;D:/Users/Kucky.ADMIN-PC/Entwicklung/Eclipse/workspace/BotTwo/Debug;D:/Users/Kucky.ADMIN-PC/Entwicklung/Eclipse/workspace/BotTwo/Release;$cd;$pwd"
(gdb)
10 info threads
&"info threads\n"
&"No registers.\n"
10^error,msg="No registers."
(gdb)
11-data-list-register-names
11^done,register-names=["r0","r1","r2","r3","r4","r5","r6","r7","r8","r9","r10","r11","r12","r13","r14","r15","r16","r17","r18","r19","r20","r21","r22","r23","r24","r25","r26","r27","r28","r29","r30","r31","SREG","SP","PC"]
(gdb)
12-break-insert _BotTwo.cpp:65
&"No symbol table is loaded. Use the \"file\" command.\n"
No symbol table is loaded. Use the "file" command.
12^error,msg="No symbol table is loaded. Use the \"file\" command."
(gdb)
13-break-insert _BotTwo.cpp:37
&"No symbol table is loaded. Use the \"file\" command.\n"
13^error,msg="No symbol table is loaded. Use the \"file\" command."
No symbol table is loaded. Use the "file" command.
(gdb)
14-gdb-exit
```