

SVETLANA TECHNICAL DATA

6N1P

Dual Audio Triode



The Svetlana™ 6N1P is a miniature glass-envelope small-signal dual triode intended for use as a line-level amplifier or driver in high-quality audio amplifiers. Except for higher heater-current consumption, it is a direct plug-in replacement for the 6DJ8, ECC88 or 6922 in most high-level audio applications. Features include very low distortion—optimized for line stages; medium transconductance; internally shielded between sections, allowing their use at differing signal levels; higher plate-voltage and dissipation rating than 6DJ8 types; and larger cathode than 6DJ8 types, giving it longer life and more transient current capability.

Characteristics

Electrical

Cathode	Oxide-coated, unipotential	
Heater voltage (AC or DC)	6.3 volts AC or DC (± 0.6 volts)	
Heater current	600 mA \pm 35 mA	
Heater-cathode voltage	± 100 volts peak	
Amplification factor (nominal)	33	
Transconductance (nominal)	7500	μS
Plate resistance (nominal)	4400	ohms
Interelectrode capacitances (typical), per section, with cathode grounded:		
Grid to cathode	3.2	pF
Anode to cathode	1.5	pF
Grid to anode	1.6	pF



Mechanical

Base	standard 9-pin miniature, glass button	
Basing diagram	JEDEC 9AJ	
Socket	9-pin miniature	
Operating position	Any	
Nominal dimensions:		
Height of glass envelope	49 mm (1.93 in.)	
Diameter of glass envelope	22.5 mm (.88 in.)	
Overall height	56 mm (2.20 in.)	
Net weight	15 g (.50 oz.)	

Maximum ratings

Anode voltage, DC	250	V
Anode dissipation, per triode	2.2	W
Cathode current, continuous, per triode	20	mA
Maximum grid-circuit resistance	0.5	megohm

Svetlana Outline drawing



Svetlana
ELECTRON DEVICES

Headquarters:

8200 South Memorial Parkway
Huntsville, AL 35802
USA
Phone: 205 882 1344
Fax: 205 880 8077

Marketing & Engineering:

3000 Alpine Road
Portola Valley, CA 94028
USA
Phone: 415 233 0429
Fax: 415 233 0439

www.svetlana.com

9/97

Svetlana 6N1P Dual Audio Triode

