

TFT PROTO™

Manual

All Mikroelektronika's development systems feature a large number of peripheral modules expanding microcontroller's range of application and making the process of program testing easier. In addition to these modules, it is also possible to use numerous additional modules linked to the development system through the I/O port connectors. Some of these additional modules can operate as stand-alone devices without being connected to the microcontroller.

Additional Board

 **MikroElektronika**

SOFTWARE AND HARDWARE SOLUTIONS FOR EMBEDDED WORLD ...making it simple

TFT PROTO

The TFT PROTO additional board is used to display graphic contents such as images and video recordings. This board is connected to the microcontroller via parallel or serial SPI communication. This board may also serve as a touch panel.

Key features:

- 320x240 display resolution;
- 262.000 colours;
- Touch panel;
- Backlight; and
- 3.3V power supply voltage.



Figure 1: TFT PROTO additional board

How to connect the board?

The TFT PROTO board is connected to a microcontroller or some other device via pads CN1. Prior to supply the power supply voltage to the backlight pins (LED-A and LED-K), it is necessary to connect an external resistor to the LED-A pin. The function of this resistor is to limit current that can damage the TFT display. When connecting the touch panel, it is necessary to connect pull-up or pull-down resistors to X+, X-, Y+ and Y- pins.

How to use the board?

The additional board may be configured to receive data from the microcontroller in one of five modes. Mode selection is performed by supplying the appropriate logic level (logic 1 (VCC-3.3) or logic 0 (GND)) on pins IM0, IM1, IM2 and IM3. Data transfer is performed via parallel or serial interface, table 1. Data from the touch panel are sent to X+, X-, Y+ and Y- pins provided on the additional board, table 2.

IM[3:0]	INTERFACE MODE	USED PINS
0010	16-BIT INTERFACE	DB[17:10], DB[8:1]
0011	8-BIT INTERFACE	DB[17:10]
010X	SPI	SDI, SDO
1010	18-BIT INTERFACE	DB[17:0]
1011	9-BIT INTERFACE	DB[17:9]

Table 1

TOUCHPANEL DRIVER	
X+	RIGHT SIDE
Y+	DOWN SIDE
X-	LEFT SIDE
Y-	UP SIDE

Table 2




Figure 2: TFT PROTO additional board connection schematic




Figure 3: Back side of the TFT PROTO additional board




Figure 4: Dimensions of the TFT PROTO additional board



MikroElektronika
SOFTWARE AND HARDWARE SOLUTIONS FOR EMBEDDED WORLD ...making it simple

If you want to learn more about our products, please visit our website at www.mikroe.com

If you are experiencing some problems with any of our products or just need additional information, please place your ticket at www.mikroe.com/en/support

If you have any questions, comments or business proposals, do not hesitate to contact us at office@mikroe.com