

Digital Storage Oscilloscopes W2000 Series

W2000 Series Oscilloscopes with full VGA Color LCD. State-of-the-art Engineered. Competitive Priced.

The W2000 Series digital storage oscilloscopes feature a large 6.4" full VGA color liquid crystal display to visualize measured waveforms at a maximum display resolution of 640 x 480 dots and is the lowest priced scope in its class.

It even is available for a price of a quarter VGA scope.

Deep 16 KB memory depth per channel enables the user to analyze long recording waveforms in detail using the pan & zoom functions.

It is the world-slimmest DSO available in its class with a thickness of only 92 mm to fit a suitcase comfortable.



Digital equals Analog

With up to 200 MHz bandwidth and 1 GSa/s sampling rate per channel, no other full VGA color resolved digital storage oscilloscope offers as much bandwidth and memory depth for the price.

The W2000 Series oscilloscopes provide accurate real-time acquisition up to their full bandwidth, advanced triggers to isolate signals of interest and various automatic measurements are standard on all models.

Their Fast Fourier Transform (FFT) math function allows the user to analyze, characterize, and troubleshoot circuits by viewing frequency and signal strength.

Features and Benefits

- 100 MHz and 200 MHz Bandwidth
- Real-Time Sample Rates up to 1 GSa/s per channel
- 2 or 4 Channels
- large 6.4" full VGA color LCD (640 x 480 dots)
- deep 16 KB Memory Depth per Channel
- 64 complete stored signal channels storable for reference and further analysis
- Autoset Menu with Waveform Selection
- Normal and Delayed Time Base
- Advanced Triggers, Including Pulse Width Trigger and Video Trigger
- Automatic Measurements
- Multi-language User Interface
- Waveform and Setup Memories
- FFT Standard on All Models
- RS232 and USB Interface to PC
- PC Application Software included

Applications

- Design and Debug
- Education and Training
- Manufacturing Test and Quality Control
- Service and Repair

Specifications

W2000 Series

Model	W2012	W2014	W2022	W2024
Display (LCD)	6.4" full VGA color display 640 x 480 dots (all models)			
Bandwidth	100 MHz	100 MHz	200 MHz	200 MHz
Channels	2	4	2	4
External Trigger Input	Standard on all models			
Sample Rate On Each Channel	1 GSa/s real-time sampling per channel			
Record Length	16 K points per channel			
Vertical Resolution	8-bits			
Vertical Sensitivity	2 mV to 5V/div			
DC Vertical Accuracy	± 3%			
Vertical Zoom	Vertically expand or compress a live or stopped waveform			
Max Input Voltage	300 VRMS CAT II			
Position Range	at 2 mV/div to 200 mV/div ± 2V; at >200 mV/div to 5 V/div ± 50 V			
BW Limit	20 MHz			
Input Coupling	AC, DC, GND			
Input Impedance	1 M Ω parallel with 15 pF			
Time Base Range	5 ns to 50 sec/div			
Time Base Accuracy	50 ppm			
Horizontal Zoom	Horizontal expand or compress a live or stopped waveform			
Net List Price in US\$, shipment free of charge within the U.S.	1,440.00	1,680.00	1,920.00	2,160.00

Acquisition Modes

- Peak Detect
High frequency and random glitch capture 10 ns (typical).
- Sample
Sample data only
- Average
Waveform averaged, selectable:
4, 16, 64, 128
- Single Shot
Use the single shot button to capture a single triggered full bandwidth single shot acquisition with up to 1 GSa/s per channel real-time sampling rate.

Trigger System

- Trigger Modes
Edge (rising or falling) – Conventional level-driven trigger. Positive or negative slope on any channel and external trigger input. Coupling selections: AC, DC, Noise Reject, HF Reject, LF Reject.
- Video
Trigger on External Channel, odd/even or all fields from composite video or broadcast standards (NTSC, PAL, SECAM)
- Pulse Width (or Glitch)
Trigger on a pulse width less than, greater than, equal to, or not equal to a selectable time limit ranging from 10 ns to 10 sec.

Trigger Source

- 2-channel models:
CH1, CH2 and External Channel
- 4-channel models:
CH1, CH2, CH3, CH4 and External Channel

Cursors

- Cursors measure absolute as well as difference voltage.

Measurements

- V, ΔV (frequency)

Measurement System

- Automatic Waveform Measurements
Period, Frequency, Max, Min, Peak-to-Peak, Mean, RMS

Waveform Processing

- Operations
Add, Subtract, FFT
- FFT – Hanning, Flat Top, Rectangular
- 16,000 sample points
- Sources – 2-channel models:
CH1 - CH2, CH2 - CH1,
CH1 + CH2
- Sources – 4-channel models:
CH1 - CH2, CH2 - CH1,
CH1 + CH2, CH3 - CH4,
CH4 - CH3, CH3 + CH4
- Autoset Menu
Single-button, automatic setup of all channels for vertical, horizontal and trigger systems.

Display Characteristics

- Full VGA Display
Color VGA resolution (640 x 480 dots), 6.4" large, active TFT color LCD
- Interpolation – $\sin(x)/x$
- Display Types – Dots, Vectors
- Persistence – Off, 1 sec, 2 sec, 5 sec, infinite
- Format – YT and XY

Environmental and Safety

- Temperature
Operating: 0°C to 50°C
Nonoperating: -40°C to 70°C
- Humidity – Operating and Nonoperating:
Up to 90% RH at or below 30°C
Operating: Up to 60% RH up to 50°C
Nonoperating: Up to 60% RH up to 55°C
- Altitude – Operating and Nonoperating:
Up to 3,000 m (10,000 ft)
- Electromagnetic Compatibility: Meets or exceed EN55011 Class A Radiated and Conducted Emissions; FCC 47 CFR, Part 15, Subpart B, Class A
- Safety
CSA61010-1, IEC61010-1, EN61010-1

Dimensions

- Instrument

Width	330 mm	13.0 in.
Height	166 mm	6.5 in.
Depth	92 mm	3.6 in.
Weight	2.3 kg	5 lbs.
- Package

Width	476 mm	18.75 in.
Height	267 mm	10.50 in.
Depth	286 mm	9.00 in.
Weight	2.8 kg	6 lbs

Ordering Information

- W2012, W2022, W2014 and W2024
- Shipment includes:
Probe (one per channel), one probe for external trigger, User manual, Power cord, USB Cable and PC Software

Wittig Technologies Support Completes the Solution.

We know you depend on Wittig instrument solutions when you make and meet critical commitments. So we make and meet a support commitment you can depend on.

Anytime you need support, anywhere in the world, Wittig Support gives you the lowest possible exposure to inconvenience, delay or disruption of operations.

- Unsurpassed technical expertise and experience with 24-hour response to technical questions
- Online support to request assistance, check service status or arrange for training
- Industry-leading turn-around service time
- 3 years warranty
- No fine print, no exclusions, no surprises
- Global Support
- Depend on Wittig Technologies. Visit www.wittigtechnologies.com/support

All products are manufactured in ISO registered facilities.

Made in Germany

Exclusive and General Importer, USA

Wittig Test Technology, Inc. USA
266 East Meadow Ave
East Meadow, NY 11554
Phone (516) 794 4344
Fax (516) 908 7758

Developer and Manufacturer, Germany

Wittig Technologies AG
Otto-Lilienthal-Str. 36
D-71034 Boeblingen
Phone +49 7031 714760
Fax +49 7031 714765

Our most up-to-date product information is available at:

www.wittigtechnologies.com

Authorized Exclusive Distributors:

Algeria +213 21 856 310
Australia 1300 853 407
Benelux +31(0)172 423 000
Bosnia & Herzegovina +385 / 1 / 2989-533
Brazil (41) 3014-3600
Bulgaria +359-2983-5928
Croatia +385 / 1 / 2989 - 533
Finland +358 9 6963 720
Hungary (1) 481 - 1231
Ireland +353 (0) 41 685 7870
Iran +98-21-2254 8717
Israel +972 3 7657348
Italy +39 02 95029266
Japan +81 3-3251-1779
Kazakhstan 044/5656784
Lebanon +961-1-311150
Luxembourg +31(0)172 423 000
Macedonia +385 / 1 / 2989 - 533
Malaysia +603 20788213
Montenegro +385 / 1 / 2989 - 533
Netherlands +31(0)172 423 000
New Zealand 1300 853 407
Pakistan +92-(0)42 - 111 100 800
Paraguay (595 21) 940 080 R.A.
Portugal +351-228329400
Poland (022) 641 15 47
Russia +7 495 796 9125
Serbia +385 / 1 / 2989 - 533
Singapore 65-67492803
Slovenia +385 / 1 / 2989 - 533
South Africa +27 11 266 1572
South Korea +(02)866-3506
Spain +34 93-430 15 97
Switzerland +41 (0)44 787 10 00
Thailand +66-2514-1000
Turkey +90(212)237 8668
United Arab Emirates +971 (6) 557 38 16
Ukraine 044/5656784
United Kingdom +1234 856345
USA see separate list

Copyright ©2006, Wittig Technologies AG, Germany. All rights reserved.
Wittig products are covered by EU and foreign patents, issued or pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved.
Wittig Technologies logos and trademarks are registered by Wittig Technologies AG, Germany and/or Wittig Test Technology, Inc. USA. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

Wittig Oscilloscope Series W2000 versus Tektronix Oscilloscope Series TDS2000

6 Top Competitive Arguments To Chose Wittig

- 1) Up to 40% less expensive list price than Tektronix TDS2000 Series (based on Tektronix U.S. List Price).
Wittig includes USB PC Application Software and huge signal storage for reference and further analysis.
- 2) Large 6.4" full VGA color LCD (TDS2000 has only 1/4 VGA resolution and only measures 5.7")
- 3) 16 KB Memory Depth per channel (TDS2000 has only 2.5 KB per channel)
- 4) World-Slimmest DSO in its class (92 mm deep housing will fit any suitcase)
- 5) All oscilloscopes include a matching bandwidth probe for every input including the external trigger.
Probes are x1/x10 switchable.
- 6) 3 years warranty

Features (per channel)	Wittig W2012	Tektronix TDS2012	Wittig W2022	Tektronix TDS2022	Wittig W2014	Tektronix TDS2014	Wittig W2024	Tektronix TDS2024
Display	Full VGA Color	Quarter VGA Color	Full VGA Color	Quarter VGA Color	Full VGA Color	Quarter VGA Color	Full VGA Color	Quarter VGA Color
Display Resolution	640 x 480 dots	320 x 240 dots	640 x 480 dots	320 x 240 dots	640 x 480 dots	320 x 240 dots	640 x 480 dots	320 x 240 dots
Display Size	6.4"	5.7"	6.4"	5.7"	6.4"	5.7"	6.4"	5.7"
Channels	2	2	2	2	4	4	4	4
Real-Time Sampling	1 GSa/s	1 GSa/s	1 GSa/s	2 GSa/s	1 GSa/s	1 GSa/s	1 GSa/s	2 GSa/s
Sampling Rate Single Shot	1 GSa/s	1 GSa/s	1 GSa/s	2 GSa/s	1 GSa/s	1 GSa/s	1 GSa/s	2 GSa/s
Analog Bandwidth	100 MHz	100 MHz	200 MHz	200 MHz	100 MHz	100 MHz	200 MHz	200 MHz
Record Length	16 K points	2.5 K points	16 K points	2.5 K points	16 K points	2.5 K points	16 K points	2.5 K points
Country of Origin	Made in Germany	China	Made in Germany	China	Made in Germany	China	Made in Germany	China
List Price	\$ 1,440.00	\$ 1,600.00	\$ 1,920.00	\$ 2,400.00	\$ 1,680.00	\$ 2,000.00	\$ 2,160.00	\$ 2,800.00
Probes included	3	2 (1x \$ 100.00)	3	2 (1x \$ 100.00)	5	4 (1x \$ 100.00)	5	4 (1x \$ 100.00)
Waveform Storage	64x 16 K	2x 2.5 K (96x more \$ 350.00)	64x 16 K	2x 2.5 K (96x more \$ 350.00)	64x 16 K	4x 2.5 K (96x more \$ 350.00)	64x 16 K	4x 2.5 K (96x more \$ 350.00)
PC Software	via USB included	via RS232 or GPIB (\$ 350.00)	via USB included	via RS232 or GPIB (\$ 350.00)	via USB included	via RS232 or GPIB (\$ 350.00)	via USB included	via RS232 or GPIB (\$ 350.00)
List Price Corrected	\$ 1,440.00	\$ 2,400.00	\$ 1,920.00	\$ 3,200.00	\$ 1,680.00	\$ 2,800.00	\$ 2,160.00	\$ 3,600.00
Difference to Tek	Save 40%	-	Save 40%	-	Save 40%	-	Save 40%	-

All prices are in US\$ and do not include any taxes. Specification and price change privileges reserved. Tektronix and Tek are registered trademarks of Tektronix, Inc.