

**Windows®. Life without Walls™.**  
**Fujitsu recommends Windows 7.**

# DATASHEET

## FUJITSU CELSIUS R670

### WORKSTATION

#### THE NEW UNCOMPROMISING HIGH-END WORKSTATION

The CELSIUS R series is the dual-processor platform for the mid-range and high-end segment with a great selection of graphics subsystems. Through the combination of standard-setting microprocessor technology and energy efficiency, the generous CELSIUS R670, with its numerous expansion options, is the ideal system for memory-consuming applications. The CELSIUS R670 is the ideal choice for business segments, such as computer aided design and engineering, mechanical design, simulation, virtual reality, visualization, digital content creation and finance.

**PERFORMANCE**

Higher productivity

- High performance multi-core processors, hard disk drives and next generation graphics subsystems

**ERGONOMICS**

Quiet system for a pleasant working environment

- Optimized thermal management, low-noise chassis and silent fans

**RELIABILITY**

System stability for the complete lifecycle

- High product standards thanks to top-quality components and comprehensive testing in certified in-house laboratories for 24/7 operation

**CERTIFICATION OF WORKSTATION APPLICATIONS**



Stability, compatibility and performance for the main workstation applications

- Comprehensive support for ISV applications and ease of integration into existing IT networks

**EXPANDABILITY**

Excellent expandability for future demands

- Increased memory capacities of up to 96 GB



# COMPONENTS

<b>PROCESSOR</b>	Intel® Xeon® processor X5570 (4C, 2.93 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor X5560 (4C, 2.8 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor X5550 (4C, 2.66 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor W5590 (4C, 3.33 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor W5580 (4C, 3.2 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor L5530 (4C, 2.40 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor L5520 (4C, 2.26 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor L5506 (4C, 2.13 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor E5540 (4C, 2.53 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor E5530 (4C, 2.4 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor E5520 (4C, 2.26 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor E5506 (4C, 2.13 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor E5504 (4C, 2.0 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor E5502 (2C, 1.86 GHz, 4 MB, 4.8 GT/s)
<b>OPERATING SYSTEM</b>	
<b>Operating system optional preinstalled</b>	Genuine Windows® 7 Professional 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows Vista® Business 64-bit Genuine Windows Vista® Business 32-bit
<b>Operating system compatible</b>	Genuine Windows® XP Professional x64 Edition Genuine Windows® XP Professional Linux
<b>Operating system notes</b>	Red Hat® certification pending Novell® certification pending For some configurations third party drivers are currently not available or configuration restrictions may apply.
<b>MEMORY MODULES</b>	
	1 GB (1 module(s) 1 GB) DDR3-SDRAM, unbuffered, ECC, 1333 MHz, PC3-10600
	1 GB (1 module(s) 1 GB) DDR3-SDRAM, unbuffered, non-ECC, 1066 MHz, PC3-8500
	2 GB (1 module(s) 2 GB) DDR3-SDRAM, registered, ECC, 1333 MHz, PC3-10600
	2 GB (1 module(s) 2 GB) DDR3-SDRAM, unbuffered, ECC, 1333 MHz, PC3-10600
	4 GB (1 module(s) 4 GB) DDR3-SDRAM, registered, ECC, 1333 MHz, PC3-10600
	4 GB (1 module(s) 4 GB) DDR3-SDRAM, unbuffered, ECC, 1333 MHz, PC3-10600
	8 GB (1 module(s) 8 GB) DDR3-SDRAM, registered, ECC, 1333 MHz, PC3-10600
<b>GRAPHICS ADD ON CARDS (OPTIONAL)</b>	
	Remote Graphics: CELSIUS RemoteAccess Card, PCIe x1, 2x DVI-I
	GPU computing card: NVIDIA® Tesla™ C1060, 4 GB, PCIe x16, -
	Ultra-high-end 3D: NVIDIA® Quadro® FX 5800, 4 GB, PCIe x16, 2x DL-DVI-I, DP
	Ultra-high-end 3D: NVIDIA® Quadro® FX 4800, 1.5 GB, PCIe x16, 2x DL-DVI-I, 2x DP
	High-end 3D: NVIDIA® Quadro® FX 3800, 1024 MB, PCIe x16, DL-DVI-I, 2x DP
	High-end 3D: ATI FirePro™ V7750, 1024 MB, PCIe x16, 2x DP, 1x DVI-I
	Midrange 3D: NVIDIA® Quadro® FX 1800, 768 MB, PCIe x16, DL-DVI-I, 2x DP
	Midrange 3D: NVIDIA® Quadro® FX 580, 512 MB, PCIe x16, DL-DVI-I, 2x DP
	Entry 3D: NVIDIA® Quadro® FX 380, 256 MB, PCIe x16, 2x DL-DVI-I
	Entry 3D: ATI FirePro™ V3700, 256 MB, PCIe x16, 2x DL-DVI-I
	Multi monitor 2D: NVIDIA® Quadro® NVS 295, 256 MB, PCIe x1, 2x DP
	Multi monitor 2D: 2nd NVIDIA® Quadro® NVS 295, 256 MB, PCIe x1, 2x DP
	Professional 2D: NVIDIA® Quadro® NVS 450, 512 MB, PCIe x16, 4 x DP
	Professional 2D: NVIDIA® Quadro® NVS 295, 256 MB, PCIe x16, 2x DP
	Professional 2D: NVIDIA® Quadro® NVS 290, 256 MB, PCIe x16, 2x SL DVI-I
	Professional 2D: NVIDIA® Quadro® NVS 290, 256 MB, PCIe x1, 2x SL DVI-I

<b>HARD DISK DRIVES (INTERNAL)</b>	SATA III, 10000 rpm, 600 GB, 3.5-inch internal SATA II, 10000 rpm, 300 GB, 2.5-inch, S.M.A.R.T. SATA II, 10000 rpm, 150 GB, 2.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 2000 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 750 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. HDD SAS, 15000 rpm, 600 GB, 3.5-inch internal HDD SAS, 15000 rpm, 450 GB, 3.5-inch HDD SAS, 15000 rpm, 300 GB, 3.5-inch HDD SAS, 15000 rpm, 146 GB, 3.5-inch
<b>Hard disk notes</b>	2.5-inch drives will be mounted in the 3.5-inch bays One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
<b>DRIVES (OPTIONAL)</b>	Blu-ray Disc™ Triple Writer DVD-ROM DVD Super Multi MultiCard Reader 20in1, 3.5-Inch
<b>INTERFACE ADD ON CARDS/COMPONENTS (OPTIONAL)</b>	WLAN III, 802.11g/Draft-n (Windows only) Gigabit Ethernet PCIe x1 eSATA Interface Dual serial card PCI
<b>Interface add on/component note</b>	1x eSATA interface already on board
<b>Base unit</b>	CELSIUS R670
<b>MAINBOARD</b>	
<b>Mainboard type</b>	D2618
<b>Formfactor</b>	AT03
<b>Chipset</b>	Intel® 5520, Intel® 82801JIB ICH10
<b>Processor socket</b>	LGA 1366
<b>Processor quantity maximum</b>	2
<b>Memory slots</b>	12 (6 per processor)
<b>Supported capacity RAM (max.)</b>	96 GB
<b>Memory notes</b>	In configurations with 4 GB and more the visible memory may be reduced to approximately 3.5 GB or less (for 32-bit operating systems) and configurations with 8 GB the visible memory may be reduced to approximately 7.5 GB or less (depending on system configuration).
<b>LAN</b>	2x Built-in 10/100/1000 MBit/s Realtek RTL8111
<b>Audio codec</b>	Realtek ALC663
<b>Audio features</b>	High Definition Audio
<b>I/O CONTROLLER ON BOARD</b>	
<b>Serial ATA total</b>	4
<b>SAS Controller type</b>	8 ports, LSI 1068E
<b>SAS RAID support</b>	0, 1, 10
<b>INTERFACES</b>	
<b>Audio: in (rear)</b>	1
<b>Audio: out / SPDIF (rear)</b>	2 / 1
<b>Front Audio: in</b>	1
<b>Front Audio: out</b>	1

**INTERFACES**

FireWire (IEEE1394) (front)	1
FireWire (IEEE1394) (rear)	1
Internal speakers	1
USB 2.0 total	11
USB front	2
USB rear	6
USB internal	3, thereof 1 type A
Serial (RS-232)	1 (9 pin)
Mouse / Keyboard (PS/2)	1 / 1
Ethernet (RJ-45)	2
eSATA	1
Interface Module notes	Anytime USB charge functionality

**DRIVE BAYS**

Drive bays total	7
3.5-inch internal bays	4
5.25-inch external bays	3

**SLOTS**

PCI-Express 2.0 x16	2 x (312 mm) full height
PCI-Express 2.0 x4 (mech. x8)	3 x (312 mm) full height
PCI (32-bit / 33 MHz)	1 x (312 mm) full height

**GRAPHICS**

Graphics notes	For some configurations third party drivers are currently not available or configuration restrictions may apply.
----------------	--

**ELECTRICAL VALUES**

Operating voltage range	100 - 240 V
Operating line frequency range	50 - 60 Hz
Max. output of single power supply	1000 W up to 85% efficiency

**NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)**

Noise Operation mode 4: High load	23 dB(A)
Idle mode	22 dB(A)
Office mode	23 dB(A)
Noise notes / description	depending on configuration

**DIMENSIONS / WEIGHT / ENVIRONMENTAL**

Dimensions (W x D x H)	215 x 622 x 446 mm
Weight	26 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	15 - 35°C
Operating relative humidity	10 - 75 %

**COMPLIANCE**

Product	CELSIUS R670
Model	MCL-D2618
Germany	GS depending on configuration
Europe	CE
USA/Canada	cCSAus FCC Class B
Global	RoHS (EU & China) ENERGY STAR® 5.0 Medical EMC standard IEC60601-1-2 in combination with medical kit
China	CCC
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates/default.aspx">https://sp.ts.fujitsu.com/sites/certificates/default.aspx</a>

**SECURITY**

<b>Physical security</b>	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock Seal option
<b>System security</b>	Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Dynamic USB security for full hardware USB protection Control of all USB interfaces External USB interfaces detachable separately Embedded security (TPM 1.2) - Infineon
<b>User security</b>	Optional: Access protection via internal SmartCard reader User and supervisor BIOS password Optional: SmartCase Logon+

**ADDITIONAL SOFTWARE**

<b>Additional software (optional)</b>	Drivers & Utilities DVD (DUDVD) Windows® 7 & Vista & XP CyberLink PowerDVD 9 Nero 9 Essentials XL Recovery DVD (Windows® 7) Recovery DVD (Windows Vista®) Windows® XP 64 downgrade pack Windows® XP 32 downgrade pack
---------------------------------------	---

**MANAGEABILITY**

<b>Manageability features</b>	DeskUpdate Driver management
<b>Manageability type</b>	DeskView 10.x client management including: DASH 1.1 remote system management
<b>DeskView features</b>	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration
<b>Supported standards</b>	WMI BootP (made4you) PXE
<b>Manageability link</b>	<a href="http://ts.fujitsu.com/manageability">http://ts.fujitsu.com/manageability</a>

**INPUT DEVICE / COMPONENTS**

<b>Input devices (optional)</b>	Optical USB tilt wheel mouse Keyboard Optical USB/PS2 tilt wheel mouse Space Navigator USB Space Explorer USB Space Pilot USB
---------------------------------	--

**WARRANTY**

<b>Standard Warranty</b>	3 years (depending on country)
<b>Service level</b>	On-site Service (depending on country)

**MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION**

<b>Recommended Service</b>	5x9, Response Time: Next Business Day
<b>Service Weblink</b>	<a href="http://ts.fujitsu.com/Supportservice">http://ts.fujitsu.com/Supportservice</a>

**FUJITSU PLATFORM SOLUTIONS**

In addition to Fujitsu CELSIUS R670, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

**Dynamic Infrastructures**

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

**Computing Products**

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

**Software**

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

**MORE INFORMATION**

Learn more about Fujitsu CELSIUS R670, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://ts.fujitsu.com/celsius>

**FUJITSU GREEN POLICY INNOVATION**

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



**COPYRIGHTS**

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
 Copyright © Fujitsu Technology Solutions

**DISCLAIMER**

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

**CONTACT**

FUJITSU Technology Solutions  
 Website: <http://ts.fujitsu.com>  
 2010-10-01 CE-EN