

ER9V/P

TECHNICAL SPECIFICATIONS

MODEL	ER9V/P
VOLTAGE RANGE	6.0 to 10.8 V
AVERAGE VOLTAGE	9.0 V
NOMINAL CAPACITY	1.2 Ah@1mA to 6V@25°C
MAX. DISCHARGE	35 mA continuous
PULSE CAPABILITY	Up to 100mA. Varies according to pulse characteristics, temperature, cell history and the application. Consult Beltrona.
WEIGHT	34.0 grams
OPERATING TEMP.	-55°C to 85°C
STORAGE TEMP.	-40°C to 60°C
SELF-DISCHARGE	1% per year @25°C
EXTERIOR/HOUSING	Plastic
TERMINALS/CONNECTOR	Ni-plated Miniature Snap
SAFETY	UL compliant. Material Safety Data-sheet-MSDS M001
TRANSPORTATION	Excepted from Regulations-see note 1

NOTE 1

For a complete description of transportation regulations and definitions of the transportation regulations and definitions of the transportation classifications „Excepted“ and „Class 9“

NOTE 2

100 count. Call for other variations.



FEATURES:

- Glass-to-Metal sealed
- Wide operating temperature range
- High pulse current capability
- Over 10 years service life
- Lasts up to 5X longer than ordinary 9V alkaline batteries
- Lasts up to 10X longer than Carbon-zinc batteries

APPLICATIONS:

- Medical Devices
- Music /Audio Devices
- Instrumentation
- Safety Devices
- Communication Devices
- Parking Meter
- Others

DIMENSIONS

PERFORMANCE GRAPHS

