

Pin	SEG	COM0	COM1	COM2	COM3
1	0	leer	leer	leer	leer
2		x			
3			x		
4				x	
5					x
6	1	1_4	1_3	1_2	1_1
7	2	1_5	1_6	1_7	1_8
8	3	2_2	2_1	1_10	1_9
9	4	2_3	2_4	2_5	2_6
10	5	P	leer	leer	leer
11	6	2_10	2_9	2_8	2_7
12	7	3_1	3_2	3_3	3_4
13	8	R	3_7	3_6	3_5
14	9	N	D	3_8	3_9
15	10	CITROEN	Seg_e	Seg_fe	Seg_f
16	11	Stern	Seg_d	Seg_g	Seg_a
17	12	AUTO	Seg_cd	Seg_c	Seg_bc
18	13	4_2	4_1	3_10	Seg_b
19	14	4_3	4_4	4_5	4_6
20	15	S	leer	leer	leer
21	16	4_10	4_9	4_8	4_7
22	17	5_1	5_2	5_3	leer
23	18	5_7	5_6	5_5	5_4
24	19	5_8	5_9	5_10	leer
25	20	6_4	6_3	6_2	6_1
26	21	6_5	6_6	6_7	leer
27	22	6_10	6_9	6_8	Skala
28	23	leer	leer	leer	leer
29	24	leer	leer	leer	leer
30	25	leer	leer	leer	leer

Pin1 ganz links (Pins an Unterkante, von oben gesehen)
Einstellungen HT1621B: 4COM, 1/2 Bias