

Part number: V600ME02.txt

Tue 27/Apr/2004 17:11:32

Attenuation: 7.8

Temperature: 25C

Oscillator Vcc: 5

Comments:

***** Serial Number: 1 *****

Comments:

Vt	freq	power	harm	sub	sens	Ic	
---	-----	-----	-----	-----	-----	-----	-----
0	1047.05	9.33	-35.67	-55.83	0	19.65	
1	1225.62	9.49	-21.67	-56.17	178.57	20.25	
2	1345.18	9.51	-19.17	-56.34	119.57	20.47	***
3	1440.97	9.49	-18.17	-56.34	95.78	20.27	***
4	1527.72	9.12	-17.50	-56.00	86.75	20.42	***
5	1604.83	9.14	-18.17	-56.00	77.12	20.38	***
6	1677.37	8.66	-17.33	-55.50	72.53	20.31	***
7	1746.98	8.61	-16.17	-56.34	69.62	20.25	***
8	1814.67	8.32	-15.83	-55.17	67.68	20.16	***
9	1881.88	8.08	-15.50	-54.67	67.22	20.06	***
10	1950.15	7.98	-16.00	-55.50	68.27	19.98	***
11	2018.47	7.94	-15.66	-54.33	68.32	19.87	***
12	2088.33	7.71	-15.50	-53.66	69.87	19.72	***
13	2160.07	7.44	-18.00	-53.16	71.73	19.59	***
14	2233.45	6.89	-16.50	-54.00	73.38	19.47	***
15	2303.15	6.50	-17.00	-53.83	69.7	19.44	***
16	2363.97	6.12	-16.67	-53.50	60.82	19.38	
17	2412.22	6.12	-17.34	-53.34	48.25	19.32	
18	2447.40	5.87	-17.34	-53.84	35.18	19.26	
19	2472.35	5.65	-17.33	-53.66	24.95	19.21	
20	2490.48	5.45	-16.84	-53.67	18.13	19.18	
21	2504.32	5.28	-16.50	-53.67	13.83	19.15	
22	2515.43	5.26	-16.50	-52.50	11.12	19.14	
23	2524.65	5.15	-16.17	-53.00	9.22	19.12	
24	2532.57	5.05	-16.17	-53.17	7.92	19.09	
25	2539.45	4.93	-16.17	-53.17	6.88	19.1	

Tuning Sens. from 1250 MHz to 2350 MHz is 76.97 MHz/V