

AccessibilityObject	Enabled
AccessibleDefaultActionDescription	FlatAppearance
AccessibleDescription	FlatStyle
AccessibleName	Focused
AccessibleRole	Font
AllowDrop	ForeColor
Anchor	Handle
AutoEllipsis	HasChildren
AutoScrollOffset	Height
AutoSize	Image
AutoSizeMode	ImageAlign
BackColor	ImageIndex
BackgroundImage	ImageKey
BackgroundImageLayout	ImageList
BindingContext	ImeMode
Bottom	InvokeRequired
Bounds	IsAccessible
CanFocus	IsDisposed
CanSelect	IsHandleCreated
Capture	IsMirrored
CausesValidation	LayoutEngine
ClientRectangle	Left
ClientSize	Location
CompanyName	Margin
Container	MaximumSize
ContainsFocus	MinimumSize
ContextMenu	✓ Name
ContextMenuStrip	Padding
Controls	Parent
Created	PreferredSize
Cursor	ProductName
DataBindings	ProductVersion
DialogResult	RecreatingHandle
DisplayRectangle	Region
Disposing	Right
Dock	RightToLeft
	Site
	Size
	TabIndex
	TabStop
	Tag
	Text
	TextAlign
	TextImageRelation
	Top
	TopLevelControl
	UseCompatibleTextRendering
	UseMnemonic
	UseVisualStyleBackColor
	UseWaitCursor
	Visible
	Width
	WindowTarget

Alle Eigenschaften eines Buttons

BeginInvoke(Delegate method)

BeginInvoke(Delegate method, Object[] args)
BringToFront()
Contains(Control ctl)
CreateControl()
CreateGraphics()
CreateObjRef(Type requestedType)
Dispose()
DoDragDrop(Object data, DragDropEffects allowedEffects)
DrawToBitmap(Bitmap bitmap, Rectangle targetBounds)
EndInvoke(IAsyncResult asyncResult)
✓ Equals(Object obj)
FindForm()
Focus()
GetChildAtPoint(Point pt)
GetChildAtPoint(Point pt, GetChildAtPointSkip skipValue)
GetContainerControl()
GetHashCode()
GetLifetimeService()
GetNextControl(Control ctl, Boolean forward)
GetPreferredSize(Size proposedSize)
GetType()
Hide()
InitializeLifetimeService()
Invalidate()
Invalidate(Boolean invalidateChildren)
Invalidate(Rectangle rc)
Invalidate(Rectangle rc, Boolean invalidateChildren)
Invalidate(Region region)
Invalidate(Region region, Boolean invalidateChildren)
Invoke(Delegate method)
Invoke(Delegate method, Object[] args)
NotifyDefault(Boolean value)
PerformClick()
PerformLayout()
PerformLayout(Control affectedControl, String affectedProperty)
PointToClient(Point p)
PointToScreen(Point p)
PreProcessControlMessage(Message& msg)
PreProcessMessage(Message& msg)
RectangleToClient(Rectangle r)
RectangleToScreen(Rectangle r)
Refresh()
ResetBackColor()
ResetBindings()
ResetCursor()
ResetFont()
ResetForeColor()
ResetImeMode()
ResetRightToLeft()
ResetText()
ResumeLayout()
ResumeLayout(Boolean performLayout)
Scale(Single dx, Single dy)
Scale(Single ratio)
Scale(SizeF factor)
Select()

SelectNextControl(Control ctl, Boolean forward, Boolean tabStopOnly, Boolean nested, Boolean wrap)
SendToBack()
SetBounds(Int32 x, Int32 y, Int32 width, Int32 height)
SetBounds(Int32 x, Int32 y, Int32 width, Int32 height, BoundsSpecified specified)
Show()
SuspendLayout()
ToString()
Update()

Alle Methoden eines Buttons