

===== USB Port3 =====

Connection Status : 0x01 (Device is connected)
Port Chain : 2-3
Properties : 0x01
IsUserConnectable : yes
PortIsDebugCapable : no
PortHasMultiCompanions : no
PortConnectorIsTypeC : no
ConnectionIndex : 3
CompanionIndex : 0
CompanionHubSymLnk : USB#ROOT_HUB30#5&1d9cd8c9&0&0#{f18a0e88-c30c-11d0-8815-00a0c906bed8}
CompanionPortNumber : 1

===== USB Device =====

+++++++ Device Information ++++++

Device Description : USB Serial Converter
Device Path : \\?\usb#vid_0403&pid_6001#fte3upe2#{a5dcbf10-6530-11d2-901f-00c04fb951ed}
Device ID : USB\VID_0403&PID_6001\FTE3UPE2
Hardware IDs : USB\VID_0403&PID_6001&REV_0600
USB\VID_0403&PID_6001
Driver KeyName : {36fc9e60-c465-11cf-8056-444553540000}\0016
(GUID_DEVCLASS_USB)
Driver : \SystemRoot\system32\drivers\ftdibus.sys
(Version: 2.12.28.1 Date: 2017-09-19)
Driver Inf : C:\WINDOWS\inf\oem12.inf
Legacy BusType : PNPBus
Class : USB
Class GUID : {36fc9e60-c465-11cf-8056-444553540000}
(GUID_DEVCLASS_USB)
Interface GUID : {a5dcbf10-6530-11d2-901f-00c04fb951ed}
(GUID_DEVINTERFACE_USB_DEVICE)
Service : FTDIBUS
Enumerator : USB
Location Info : Port_#0003.Hub_#0003
Location IDs :
PCIROOT(0)#PCI(1C03)#PCI(0000)#USBROOT(0)#USB(3),
ACPI(_SB_)#ACPI(PCI0)#ACPI(RP04)#ACPI(PXSX)#USBROOT(0)#USB(3)
Container ID : {6f624fca-a2ea-56d8-a451-a6b9c5b088dd}
Manufacturer Info : FTDI
Capabilities : 0x94 (Removable, UniqueID, SurpriseRemovalOK)
Status : 0x0180600A (DN_DRIVER_LOADED, DN_STARTED,
DN_DISABLEABLE, DN_REMOVABLE, DN_NT_ENUMERATOR, DN_NT_DRIVER)
Problem Code : 0
Address : 3
Power State : D0 (supported: D0, D2, D3, wake from D0, wake
from D2)
Child Device 1 : USB Serial Port (COM7)
DevicePath :
\\?\ftdibus#vid_0403+pid_6001+fte3upe2a#0000#{86e0d1e0-8089-11d0-9ce4-08003e301f73}
KernelName : \Device\000000e7
Device ID : FTDIBUS\VID_0403+PID_6001+FTE3UPE2A\0000
Class : Ports
COM-Port : COM7 (\Device\VCP0)

+++++++ Registry USB Flags ++++++

HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\usbflags\040360010600

osvc : REG_BINARY 00 00
SkipContainerIdQuery : REG_BINARY 01 00 00 00

----- Connection Information -----
Connection Index : 0x03 (3)
Connection Status : 0x01 (DeviceConnected)
Current Config Value : 0x01
Device Address : 0x01 (1)
Is Hub : 0x00 (no)
Device Bus Speed : 0x01 (Full-Speed)
Number Of Open Pipes : 0x02 (2 pipes to data endpoints)
Pipe[0] : EndpointID=1 Direction=IN ScheduleOffset=0
Type=Bulk
Pipe[1] : EndpointID=2 Direction=OUT ScheduleOffset=0
Type=Bulk
Data (HexDump) : 03 00 00 00 12 01 00 02 00 00 00 08 03 04 01 60
.....
00 06 01 02 03 01 01 01 00 01 00 02 00 00 00 01
.....
00 00 00 07 05 81 02 40 00 00 00 00 00 00 07 05
.....@.....
02 02 40 00 00 00 00 00 00
..@.....

----- Connection Information V2 -----
Connection Index : 0x03 (3)
Length : 0x10 (16 bytes)
SupportedUsbProtocols : 0x03
 Usb110 : 1 (yes)
 Usb200 : 1 (yes)
 Usb300 : 0 (no)
 ReservedMBZ : 0x00
Flags : 0x00
 DevIsOpAtSsOrHigher : 0 (Is not operating at SuperSpeed or higher)
 DevIsSsCapOrHigher : 0 (Is not SuperSpeed capable or higher)
 DevIsOpAtSsPlusOrHigher : 0 (Is not operating at SuperSpeedPlus or higher)
 DevIsSsPlusCapOrHigher : 0 (Is not SuperSpeedPlus capable or higher)
 ReservedMBZ : 0x00
Data (HexDump) : 03 00 00 00 10 00 00 00 03 00 00 00 00 00 00 00
.....

----- Device Descriptor -----
bLength : 0x12 (18 bytes)
bDescriptorType : 0x01 (Device Descriptor)
bcdUSB : 0x200 (USB Version 2.00)
bDeviceClass : 0x00 (defined by the interface descriptors)
bDeviceSubClass : 0x00
bDeviceProtocol : 0x00
bMaxPacketSize0 : 0x08 (8 bytes)
idVendor : 0x0403 (Future Technology Devices International Limited)
idProduct : 0x6001
bcdDevice : 0x0600
iManufacturer : 0x01 (String Descriptor 1)
 Language 0x0409 : "FTDI"
iProduct : 0x02 (String Descriptor 2)
 Language 0x0409 : "TTL232R-3V3"
iSerialNumber : 0x03 (String Descriptor 3)
 Language 0x0409 : "FTE3UPE2"
bNumConfigurations : 0x01 (1 Configuration)
Data (HexDump) : 12 01 00 02 00 00 00 08 03 04 01 60 00 06 01 02
.....

..

```

----- Configuration Descriptor -----
bLength           : 0x09 (9 bytes)
bDescriptorType   : 0x02 (Configuration Descriptor)
wTotalLength      : 0x0020 (32 bytes)
bNumInterfaces    : 0x01 (1 Interface)
bConfigurationValue : 0x01 (Configuration 1)
iConfiguration    : 0x00 (No String Descriptor)
bmAttributes      : 0x80
  D7: Reserved, set 1 : 0x01
  D6: Self Powered   : 0x00 (no)
  D5: Remote Wakeup  : 0x00 (no)
  D4..0: Reserved, set 0 : 0x00
MaxPower          : 0x2D (90 mA)
Data (HexDump)    : 09 02 20 00 01 01 00 80 2D 09 04 00 00 02 FF FF
.. ..-.....
                      FF 02 07 05 81 02 40 00 00 07 05 02 02 40 00 00
.....@.....@..

```

```

----- Interface Descriptor -----
bLength           : 0x09 (9 bytes)
bDescriptorType   : 0x04 (Interface Descriptor)
bInterfaceNumber  : 0x00
bAlternateSetting : 0x00
bNumEndpoints     : 0x02 (2 Endpoints)
bInterfaceClass   : 0xFF (Vendor Specific)
bInterfaceSubClass : 0xFF
bInterfaceProtocol : 0xFF
iInterface        : 0x02 (String Descriptor 2)
  Language 0x0409 : "TTL232R-3V3"
Data (HexDump)    : 09 04 00 00 02 FF FF FF 02
.....

```

```

----- Endpoint Descriptor -----
bLength           : 0x07 (7 bytes)
bDescriptorType   : 0x05 (Endpoint Descriptor)
bEndpointAddress  : 0x81 (Direction=IN EndpointID=1)
bmAttributes      : 0x02 (TransferType=Bulk)
wMaxPacketSize    : 0x0040 (64 bytes)
bInterval         : 0x00 (ignored)
Data (HexDump)    : 07 05 81 02 40 00 00
....@..

```

```

----- Endpoint Descriptor -----
bLength           : 0x07 (7 bytes)
bDescriptorType   : 0x05 (Endpoint Descriptor)
bEndpointAddress  : 0x02 (Direction=OUT EndpointID=2)
bmAttributes      : 0x02 (TransferType=Bulk)
wMaxPacketSize    : 0x0040 (64 bytes)
bInterval         : 0x00 (ignored)
Data (HexDump)    : 07 05 02 02 40 00 00
....@..

```

```

----- Device Qualifier Descriptor -----
Error             : ERROR_GEN_FAILURE

```

```

----- String Descriptors -----
----- String Descriptor 0 -----
bLength           : 0x04 (4 bytes)
bDescriptorType   : 0x03 (String Descriptor)
Language ID[0]    : 0x0409 (English - United States)

```

```

Data (HexDump)          : 04 03 09 04
....
----- String Descriptor 1 -----
bLength                 : 0x0A (10 bytes)
bDescriptorType         : 0x03 (String Descriptor)
Language 0x0409        : "FTDI"
Data (HexDump)         : 0A 03 46 00 54 00 44 00 49 00
..F.T.D.I.
----- String Descriptor 2 -----
bLength                 : 0x18 (24 bytes)
bDescriptorType         : 0x03 (String Descriptor)
Language 0x0409        : "TTL232R-3V3"
Data (HexDump)         : 18 03 54 00 54 00 4C 00 32 00 33 00 32 00 52 00
..T.T.L.2.3.2.R.
                        2D 00 33 00 56 00 33 00
-.3.V.3.
----- String Descriptor 3 -----
bLength                 : 0x12 (18 bytes)
bDescriptorType         : 0x03 (String Descriptor)
Language 0x0409        : "FTE3UPE2"
Data (HexDump)         : 12 03 46 00 54 00 45 00 33 00 55 00 50 00 45 00
..F.T.E.3.U.P.E.
                        32 00
2.

```