

Standard Open & Encapsulated Toroidal Transformers

Features

- Single 230V & Dual 2x115V, 50/60Hz Primary
- Lower Strayfield and high efficiency
- Small size and low weight
- Extremely low level of radiated magnetic field
- Very low induced noise (hum)
- Very low iron loss
- Supplied with mounting kit
- Test Voltage Primary - Secondary 4.5 KV
- 100% electrical and flash tested
- Manufactured in an ISO 9001:2015 and ISO 14001:2015 certified Talema facility
- Fully RoHS & REACH Compliant



Power VA	Part Number	Secondary		
	Primary 230V	Full Load V	Current A	Open Circuit V
15	0015P1-2-006	2 x 6	1.25	2 x 7.0
	0015P1-2-009	2 x 9	0.83	2 x 10.5
	0015P1-2-012	2 x 12	0.63	2 x 14.0
	0015P1-2-015	2 x 15	0.50	2 x 17.4
	0015P1-2-018	2 x 18	0.42	2 x 21.1
30	0030P1-2-006	2 x 6	2.50	2 x 7.2
	0030P1-2-009	2 x 9	1.67	2 x 10.6
	0030P1-2-012	2 x 12	1.25	2 x 14.1
	0030P1-2-015	2 x 15	1.00	2 x 17.6
	0030P1-2-018	2 x 18	0.83	2 x 21.2
	0030P1-2-022	2 x 22	0.68	2 x 26.0
50	0050P1-2-006	2 x 6	4.17	2 x 6.8
	0050P1-2-009	2 x 9	2.78	2 x 10.2
	0050P1-2-012	2 x 12	2.08	2 x 13.6
	0050P1-2-015	2 x 15	1.67	2 x 17.1
	0050P1-2-018	2 x 18	1.39	2 x 20.4
	0050P1-2-022	2 x 22	1.14	2 x 24.9
	0050P1-2-055	2 x 55	0.45	2 x 62.4
80	0080P1-2-010	2 x 10	4.00	2 x 11.5
	0080P1-2-012	2 x 12	3.33	2 x 13.8
	0080P1-2-015	2 x 15	2.67	2 x 17.3
	0080P1-2-018	2 x 18	2.22	2 x 20.7
	0080P1-2-022	2 x 22	1.82	2 x 25.4
120	0120P1-2-012	2 x 12	5.00	2 x 13.4
	0120P1-2-015	2 x 15	4.00	2 x 16.8
	0120P1-2-018	2 x 18	3.33	2 x 20.2
	0120P1-2-022	2 x 22	2.73	2 x 24.5
	0120P1-2-055	2 x 55	1.03	2 x 61.3

Note:

Standard Encapsulated versions available from 15VA to 500VA
See following page for dimensions and specifications

Ordering Information

Example: 0030 P1 -2 -012 -K

Power (VA) ——— Polyamid Housing
Number of ——— Secondary Voltage
Primaries ——— Number of Secondaries


Power VA	Part Number	Secondary		
	Primary 230V	Full Load V	Current A	Open Circuit V
160	0160P1-2-012	2 x 12	6.67	2 x 13.5
	0160P1-2-015	2 x 15	5.33	2 x 16.6
	0160P1-2-018	2 x 18	4.44	2 x 20.0
	0160P1-2-022	2 x 22	3.64	2 x 24.5
	0160P1-2-030	2 x 30	2.67	2 x 33.5
	0160P1-2-055	2 x 55	1.45	2 x 61.2
225	0225P1-2-012	2 x 12	9.38	2 x 13.1
	0225P1-2-015	2 x 15	7.50	2 x 16.5
	0225P1-2-018	2 x 18	6.25	2 x 19.7
	0225P1-2-022	2 x 22	5.11	2 x 24.2
	0225P1-2-024	2 x 24	4.69	2 x 26.5
	0225P1-2-030	2 x 30	3.75	2 x 32.8
300	0300P1-2-012	2 x 12	12.5	2 x 13.1
	0300P1-2-018	2 x 18	8.33	2 x 19.4
	0300P1-2-022	2 x 22	6.82	2 x 23.8
	0300P1-2-025	2 x 25	6.00	2 x 27.1
	0300P1-2-030	2 x 30	5.00	2 x 32.5
	0300P1-2-035	2 x 35	4.29	2 x 37.8
	0300P1-2-055	2 x 55	2.73	2 x 59.6
	0500P1-2-020	2 x 20	12.5	2 x 21.5
500	0500P1-2-025	2 x 25	10.0	2 x 26.7
	0500P1-2-030	2 x 30	8.33	2 x 32.3
	0500P1-2-040	2 x 40	6.25	2 x 43.0
	0500P1-2-055	2 x 55	4.55	2 x 59.0
	0625P1-2-018	2 x 18	17.4	2 x 19.3
625	0625P1-2-022	2 x 22	14.2	2 x 23.5
	0625P1-2-040	2 x 40	7.81	2 x 42.8
	0625P1-2-045	2 x 45	6.94	2 x 48.3
	0625P1-2-050	2 x 50	6.25	2 x 53.8
	0625P1-2-055	2 x 55	5.68	2 x 58.9
	0625P1-4-012	4 x 12	13.00	4 x 12.9
800	0800P1-2-040	2 x 40	10.00	2 x 42.4
	0800P1-2-045	2 x 45	8.89	2 x 47.6
	0800P1-2-050	2 x 50	8.00	2 x 52.9
	0800P1-2-055	2 x 55	7.27	2 x 58.1
1000	1000P1-2-018	2 x 18	27.8	2 x 18.8
	1000P1-2-018	2 x 18	27.8	2 x 18.8
	1000P1-2-022	2 x 22	22.7	2 x 23.5
	1000P1-2-040	2 x 40	12.5	2 x 42.2
	1000P1-2-045	2 x 45	11.1	2 x 47.5
	1000P1-2-050	2 x 50	10.0	2 x 52.8
	1000P1-2-055	2 x 55	9.09	2 x 58.1
	1000P1-4-022	4 x 22	11.4	4 x 23.5
	1000P1-4-028	4 x 28	8.93	4 x 29.3

Standard Open & Encapsulated Toroidal Transformers

Power VA	Part Number	Secondary		
	Primary 2x115V	Full Load V	Current A	Open Circuit V
15	0015P2-2-006	2 x 6	1.25	2 x 7.0
	0015P2-2-009	2 x 9	0.83	2 x 10.5
	0015P2-2-012	2 x 12	0.63	2 x 14.0
	0015P2-2-015	2 x 15	0.50	2 x 17.4
	0015P2-2-018	2 x 18	0.42	2 x 21.1
30	0030P2-2-006	2 x 6	2.50	2 x 7.2
	0030P2-2-009	2 x 9	1.67	2 x 10.6
	0030P2-2-012	2 x 12	1.25	2 x 14.1
	0030P2-2-015	2 x 15	1.00	2 x 17.6
	0030P2-2-018	2 x 18	0.83	2 x 21.2
	0030P2-2-022	2 x 22	0.68	2 x 26.0
50	0050P2-2-006	2 x 6	4.17	2 x 6.8
	0050P2-2-009	2 x 9	2.78	2 x 10.2
	0050P2-2-012	2 x 12	2.08	2 x 13.6
	0050P2-2-015	2 x 15	1.67	2 x 17.1
	0050P2-2-018	2 x 18	1.39	2 x 20.4
	0050P1-2-022	2 x 22	1.14	2 x 24.9
	0050P2-2-055	2 x 55	0.45	2 x 62.4
80	0080P2-2-010	2 x 10	4.00	2 x 11.5
	0080P2-2-012	2 x 12	3.33	2 x 13.8
	0080P2-2-015	2 x 15	2.67	2 x 17.3
	0080P2-2-018	2 x 18	2.22	2 x 20.7
	0080P2-2-022	2 x 22	1.82	2 x 25.4
120	0120P2-2-012	2 x 12	5.00	2 x 13.4
	0120P2-2-015	2 x 15	4.00	2 x 16.8
	0120P2-2-018	2 x 18	3.33	2 x 20.2
	0120P2-2-022	2 x 22	2.73	2 x 24.5
	0120P2-2-055	2 x 55	1.03	2 x 61.3


Power VA	Part Number	Secondary		
	Primary 2x115V	Full Load V	Current A	Open Circuit V
160	0160P2-2-012	2 x 12	6.67	2 x 13.5
	0160P2-2-015	2 x 15	5.33	2 x 16.6
	0160P2-2-018	2 x 18	4.44	2 x 20.0
	0160P2-2-022	2 x 22	3.64	2 x 24.5
	0160P2-2-030	2 x 30	2.67	2 x 33.5
	0160P2-2-055	2 x 55	1.45	2 x 61.2
225	0225P2-2-012	2 x 12	9.38	2 x 13.1
	0225P2-2-015	2 x 15	7.50	2 x 16.5
	0225P2-2-018	2 x 18	6.25	2 x 19.7
	0225P2-2-022	2 x 22	5.11	2 x 24.2
	0225P2-2-024	2 x 24	4.69	2 x 26.5
	0225P2-2-030	2 x 30	3.75	2 x 32.8
300	0300P2-2-012	2 x 12	12.5	2 x 13.1
	0300P2-2-018	2 x 18	8.33	2 x 19.4
	0300P2-2-022	2 x 22	6.82	2 x 23.8
	0300P2-2-025	2 x 25	6.00	2 x 27.1
	0300P2-2-030	2 x 30	5.00	2 x 32.5
	0300P2-2-035	2 x 35	4.29	2 x 37.8
	0300P2-2-055	2 x 55	2.73	2 x 59.6
500	0500P2-2-020	2 x 20	12.50	2 x 21.5
	0500P2-2-025	2 x 25	10.00	2 x 26.7
	0500P2-2-030	2 x 30	8.33	2 x 32.3
	0500P2-2-040	2 x 40	6.25	2 x 43.0
	0500P2-2-055	2 x 55	4.55	2 x 59.0
625	0625P2-2-018	2 x 18	17.4	2 x 19.3
	0625P2-2-022	2 x 22	14.2	2 x 23.5
	0625P2-2-040	2 x 40	7.81	2 x 42.8
	0625P2-2-045	2 x 45	6.94	2 x 48.3
	0625P2-2-050	2 x 50	6.25	2 x 53.8
	0625P2-2-055	2 x 55	5.68	2 x 58.9
800	0625P2-4-012	4 x 12	13.0	4 x 12.9
	0800P2-2-040	2 x 40	10.00	2 x 42.4
	0800P2-2-045	2 x 45	8.89	2 x 47.6
	0800P2-2-050	2 x 50	8.09	2 x 52.9
	0800P2-2-055	2 x 55	7.27	2 x 58.1
1000	1000P2-2-018	2 x 18	27.8	2 x 18.8
	1000P2-2-022	2 x 22	22.7	2 x 23.5
	1000P2-2-040	2 x 40	12.5	2 x 42.2
	1000P2-2-045	2 x 45	11.1	2 x 47.5
	1000P2-2-050	2 x 50	10.0	2 x 52.8
	1000P2-2-055	2 x 55	9.09	2 x 58.1
	1000P2-4-022	4 x 22	11.4	4 x 23.5
	1000P2-4-028	4 x 28	8.93	4 x 29.3

Schematic



Primary: 2 x 115V / 48 - 60Hz
for series or parallel connection
Secondary: 2 or 4xUsec
for series or parallel connection

Schematic



Primary: 230V / 48 - 60Hz
Secondary: 2 or 4xUsec
for series or parallel connection

Standard Open & Encapsulated Toroidal Transformers



Nominal Power VA	Primary			Core Loss W	Copper Loss Typical		Dimensions and weight without Mounting Disks			Potted in Polyamid Housing		
	Full Load Current A	No Load Current mA	Copper Resistance T = 20°C Ohm		T = 20°C W	T = 120°C W	Ø mm	Height* mm	Weight kg	Ø mm	Height mm	Center Hole for Mounting Bolt Ø
15	0.08	2.0	178.0	0.21	1.8	2.5	60	31	0.3	63	34.5	5.1
30	0.15	2.8	92.0	0.26	3.6	5.0	70	32	0.5	81	39	5.1
50	0.25	5.0	42.0	0.43	4.7	6.6	80	35	0.7	87	42	5.1
80	0.40	5.6	27.0	0.51	8.4	11.0	92	36	1.0	97	44	6.1
120	0.53	8.5	15.5	0.76	9.9	13.9	92	45	1.3	104	52	6.1
160	0.79	10.0	10.5	0.97	11.9	20.8	104	44	1.6	115	53	6.1
225	1.08	14.0	6.6	1.30	15.2	21.3	112	48	2.1	126	52	6.1
300	1.41	17.0	4.2	1.70	16.1	22.5	115	58	2.5	126	65	6.1
500	2.32	23.0	1.83	2.50	22.1	31.0	135	60	3.9	147	65	8.2
625	2.90	28.0	1.50	3.10	27.9	39.0	140	70	4.6	--	--	--
800	3.71	33.1	1.30	3.65	28.9	41.2	162	60	5.1	--	--	--
1000	4.56	38.0	0.88	4.80	30.7	43.0	160	72	6.9	--	--	--
* Allow an extra 3mm for mounting kit and 3-4mm to the dimensions where the leads emerge												

Material Temperature Class

Copper (Pri. & Sec) H (180°C)

Isolation between
Primary & Secondary B (130°C)

Lead isolation A (105°C)

Leads

Primary : Double insulated leads,
150mm long, 10mm stripped

Secondary : PVC insulated,
150mm long, 10mm tinned

Approvals:

Approved to EN61558 & IEC 61558

DEKRA Nr. 2161054.01 for Safety Isolation Transformers

DEKRA Nr. 2161054.02 for Isolation Transformers

Marked with the ENEC KEMA-KEUR stamp of approval

Approved to UL 5085-1 (General Purpose Transformers)

File XPTQ2.E215495 - USA

File XPTQ8.E215495 - Canada

Regional Locations - Design, Manufacturing, Sales & Marketing

Talema Group Regional Offices

North America

United States (Sales & Marketing)

Talema Group, LLC
PO Box 935
900 Innovation Drive
Suite 120, Rolla
Missouri 65402
Tel: +1 573-303-3675
E-Mail: sales@talemagroup.com
Web: www.talema.com

Administrative Office

Talema Electronic India Private Limited
Door No. 221, 1st and 2nd Floor
KJ Plaza, Opp.to Vidya Mandir School
Meyanoor Main Road
Salem - 636 004 Tamil Nadu INDIA
Tel: +91 427 - 243 3100
Fax: +91 427 - 243 3109
E-Mail: talema@talemaindia.net
Web: www.talema.com

Asia

India (Design, Manufacturing, Sales & Marketing)

Factory Premises

Talema Electronic India Private Limited
Plot Nos. 30, 31 Electrical and Electronic
Industrial Estate
Suramangalam
Salem - 636 005 Tamil Nadu INDIA
Tel: +91 427 - 243 3000
E-Mail: talema@talemaindia.net
Web: www.talema.com

Europe

Germany (Design, Sales & Marketing)

Talema Elektronik GmbH
Sembdnerstr. 5
82110 Germering
Tel: +49 89 - 841 00 - 0
Fax: +49 89 - 841 00 25
E-Mail: info@talema.de
Web: www.talema.com

Ireland (Design, Sales & Marketing)

Nuvotem TEO
Units W & X, Gweedore Business Park
Derrybeg, Letterkenny, Co. Donegal
Tel: +353 (0) 74 95 48666
Fax: +353 (0) 74 95 48139
E-Mail: info@nuvotem.com
Web: www.nuvotem.com

Czech Republic (Design, Manufacturing, Sales & Marketing)

NT Magnetics s.r.o.
Chebská 27
322 00 Plzeň
Tel: +420 377 - 338 351
Fax: +420 377 - 338 350
E-Mail: talema@talema.cz
Web: www.ntmagnetics.cz

Locations of Talema Group Regional Offices

