



in a 1593K Hammond Case

Unless otherwise specified, all values are as follows:  
 resistor values are in Ohms, i.e. 0R47, 5R6, 220, 5K6, 22K  
 capacitor values are in Microfarads, i.e. 220p, 0u1, 2u2, 33  
 inductor values are in Microhenries, i.e. 0u22, 5u6, 68, 2m2

This drawing is our property. Duplication, unauthorized use of any kind is prohibited.  
 Without Approval use only for inquiry.

PCB Name: <b>PCB Name</b>		Title: <b>FTDI_USB_RS-232 + RS-485U</b>	
PCB Nr: <b>PCB Nr</b>		Scale:	
PCB Type:		Used in:	
Date:		Repl for:	
Name: <b>Author</b>		Build No.:	
Drawn	4-Nov-2020 11:30:17	Change Index	Change Notification Nr.
Modified		Date	Name
Checked		Drw. Type:	Prj. Nr. <b>PRJ. No</b>
<input type="checkbox"/> Prototype <input type="checkbox"/> Production <input type="checkbox"/> BOM Done?		Size: <b>A3</b>	Rev: <b>0</b>
		Drw. Nr.	
		File: <b>FTDI_USB1.Sch</b>	
		Sheet <b>1</b> of <b>1</b>	

