

RJ45-Stecker Belegung nach 568 B

Ethernet 10/100 Crossover	Telefon analog	ISDN	FDDI 100	Token Ring 4/16	AS 400	3270	ATM	TP-PMD	Ethernet 1000	Ethernet 10/100	Paar	Bezeichnung
1 grün/weiss (3)	-	-	-	-	-	-	1 X	1 Tx +	1 Tx/D1+	1 Tx +	2	1 orange/weiss
2 grün (6)	-	-	-	-	-	-	2 X	2 Tx -	2 Tx/D1-	2 Tx -	2	2 orange
3 orange/weiss (1)	-	3 a2 Tx +	3 Tx +	3 Tx +	-	3 Rx +	-	-	3 Rx/D2+	3 Rx +	3	3 grün/weiss
4 blau	4 a	4 a1 Rx +	4 Rx -	4 Rx -	4 Tx +	4 Tx +	-	-	4 BI/D3+	-	1	4 blau
5 blau/weiss	5 b	5 b1 Rx -	5 Rx +	5 Rx +	5 Tx -	5 Tx -	-	-	5 BI/D3-	-	1	5 blau/weiss
6 orange (2)	-	6 b2 Tx -	6 Tx -	6 Tx -	-	6 Rx -	-	-	6 Rx/D3-	6 Rx -	3	6 grün
7 braun/weiss	-	-	-	-	-	-	7 X	7 Rx +	7 BI/D4+	-	4	7 braun/weiss
8 braun	-	-	-	-	-	-	8 X	8 Rx -	8 BI/D4-	-	4	8 braun

Klipp auf der Unterseite

