

Lexmark E330

3/1

PAPER MENU

Paper Source = Tray 1
PAPER SIZE
Tray 1 Size = A4
Manual Pap Size = A4
Manual Env. Size = DL Envelope

PAPER TYPE

Tray 1 Type = Plain Paper
Manual Pap Type = Plain Paper
Manual Env. Type = Envelope

CUSTOM TYPES

Custom Type 1 = Paper
Custom Type 2 = Paper
Custom Type 3 = Paper
Custom Type 4 = Paper
Custom Type 5 = Paper
Custom Type 6 = Envelope

UNIVERSAL SETUP

Units of Measure = Millimeters
Portrait Width = 216 mm
Portrait Height = 356 mm
Feed Direction = Short Edge
Substitute Size = All Listed

PAPER TEXTURE

Plain Texture = Normal
Card Stock Text = Normal
Trnsprncy Text = Normal
Labels Texture = Normal
Bond Texture = Rough
Envelope Texture = Normal
Ltrhead Texture = Normal
Preprint Texture = Normal
Colored Texture = Normal
Custom 1 Texture = Normal
Custom 2 Texture = Normal
Custom 3 Texture = Normal
Custom 4 Texture = Normal
Custom 5 Texture = Normal
Custom 6 Texture = Rough

PAPER WEIGHT

Plain Weight = Normal
CardStock Weight = Normal
Trnsprncy Weight = Normal
Labels Weight = Normal
Bond Weight = Normal
Envelope Weight = Normal
Ltrhead Weight = Normal
Preprint Weight = Normal
Colored Weight = Normal
Custom 1 Weight = Normal
Custom 2 Weight = Normal
Custom 3 Weight = Normal
Custom 4 Weight = Normal
Custom 5 Weight = Normal
Custom 6 Weight = Heavy

FINISHING MENU

Copies = 1
Blank Pages = Do Not Print
Collation = Off
Separator Sheets = None
Separator Source = Tray 1
Multipage Print = Off
Multipage Order = Horizontal
Multipage View = Auto
Multipage Border = None

QUALITY MENU

Print Resolution = 600 dpi
Toner Darkness = 8v...+
PictureGrade = Off

SETUP MENU

Printer Language = PCL Emulation
Power Saver = 30
Resource Save = Off
Print Timeout = 90
Wait Timeout = 40
Auto Continue = Disabled
Jam Recovery = Auto
Page Protect = Off
Print Area = Normal
Display Language = English
Toner Alarm = Off

PCL EMUL MENU

Font Source = Resident
Font Name = RO Courier
Pitch = 10.00
Symbol Set = 12U PC-850
Orientation = Portrait
Lines per Page = 64
A4 Width = 198 mm

TRAY RENUMBER

Assign Tray 1 = Off
Assign Man Paper = Off
Assign Man Env = Off

VIEW FACTORY DEF

MPF Default = 8
T1 Default = 1
T2 Default = 4
T3 Default = 5
T4 Default = 20
T5 Default = 21
Env Default = 6
MPap Default = 2
MEnv Default = 3

Auto CR after LF = Off
Auto LF after CR = Off

POSTSCRIPT MENU

Print PS Error = Off

PARALLEL MENU

PCL SmartSwitch = On
PS SmartSwitch = On
NPA Mode = Auto
Parallel Buffer = Auto
Advanced Status = On
Protocol = Fastbytes
Honor Init = Off
Parallel Mode 2 = On
MAC Binary PS = Auto

USB MENU

PCL SmartSwitch = On
PS SmartSwitch = On
NPA Mode = Auto
USB Buffer = Auto
MAC Binary PS = Auto

Other Settings

Res. Reduction = On
PCL Type 1 Fonts = On
Feed Timeout = 60
Job Timeout = Disabled

Printer Information

Page Count = 29715
Installed Memory = 32MB
Processor Speed = 200MHz
Serial Number = 3807030
Engine Speed = 27

Printer Revision Levels

Loader = 140.237-0
Basic Kernel = EAN.KA.K009-0
Base = 140.237-0
Engine = E141.441-0
Font = 8.11M01-U4.0

Cartridge Information

0% 100%
Toner Level
Photoconductor = OK
Serial Number = 0931458451
Capacity = 6K
Type = Normal
Return Program

Printing Statistics

Printer Page Count:

Total = 29715

Jobs Printed:

PCL5 Emulation = 12593
PS Emulation = 835
PCL6 Emulation = 3150
Other = 0
Total = 16578

Supplies:

Black Toner
1.5K Pages = 2
6K Pages = 10
2.5K Pages = 1

Paper Used:

Plain Paper = 29658
Transparency = 0
Labels = 0
Card Stock = 0
Letterhead = 0
Bond = 0
Preprinted = 0
Colored Paper = 0
Envelope = 0
Custom Type 1 = 0
Custom Type 2 = 0
Custom Type 3 = 0
Custom Type 4 = 0
Custom Type 5 = 0
Custom Type 6 = 0
Total = 29658