

<https://www.itu.int/rec/R-REC-P/en>

## Radiowave propagation

- P.310 Definitions of terms relating to propagation in non-ionized media
- P.311 Acquisition, presentation and analysis of data in studies of radiowave propagation
- P.313 Exchange of information for short-term forecasts and transmission of ionospheric disturbance warnings  
Note - Suppressed on 10/10/2013 (CACE/636)
- P.341 The concept of transmission loss for radio links
- P.368 Ground-wave propagation prediction method for frequencies between 10 kHz and 30 MHz
- P.369 Reference atmosphere for refraction  
Note - Suppressed on 24/10/97 (RA-97) - This Recommendation has been replaced by Rec. ITU-R P.453-6
- P.370 VHF and UHF propagation curves for the frequency range from 30 MHz to 1 000 MHz. Broadcasting services  
Note - Suppressed on 22/10/01 (CACE/233)
- P.371 Choice of indices for long-term ionospheric predictions
- P.372 Radio noise
- P.373 Definitions of maximum and minimum transmission frequencies
- P.434 ITU-R reference ionospheric characteristics and methods of basic MUF, operational MUF and ray-path prediction  
Note - Suppressed on 24/10/97 (RA-97)
- P.435 Sky-wave field-strength prediction method for the broadcasting service in the frequency range 150 to 1600 kHz  
Note - Suppressed on 20/10/95 (RA-95)
- P.452 Prediction procedure for the evaluation of interference between stations on the surface of the Earth at frequencies above about 0.1 GHz
- P.453 The radio refractive index: its formula and refractivity data  
Note - This Recommendation replaces Rec. ITU-R P.369-6
- P.525 Calculation of free-space attenuation
- P.526 Propagation by diffraction

- P.527 Electrical characteristics of the surface of the Earth
- P.528 A propagation prediction method for aeronautical mobile and radionavigation services using the VHF, UHF and SHF bands
- P.529 Prediction methods for the terrestrial land mobile service in the VHF and UHF bands  
Note - Suppressed on 22/10/01 (CACE/233)
- P.530 Propagation data and prediction methods required for the design of terrestrial line-of-sight systems
- P.531 Ionospheric propagation data and prediction methods required for the design of satellite networks and systems
- P.532 Ionospheric effects and operational considerations associated with artificial modification of the ionosphere and the radio-wave channel
- P.533 Method for the prediction of the performance of HF circuits
- P.534 Method for calculating sporadic-E field strength
- P.581 The concept of "worst month"
- P.616 Propagation data for terrestrial maritime mobile services operating at frequencies above 30 MHz  
Note - Suppressed on 22/10/01 (CACE/233)
- P.617 Propagation prediction techniques and data required for the design of trans-horizon radio-relay systems
- P.618 Propagation data and prediction methods required for the design of Earth-space telecommunication systems
- P.619 Propagation data required for the evaluation of interference between stations in space and those on the surface of the Earth
- P.620 Propagation data required for the evaluation of coordination distances in the frequency range 100 MHz to 105 GHz
- P.676 Attenuation by atmospheric gases and related effects
- P.678 Characterization of the variability of propagation phenomena and estimation of the risk associated with propagation margin
- P.679 Propagation data required for the design of broadcasting-satellite systems
- P.680 Propagation data required for the design of Earth-space maritime mobile telecommunication systems
- P.681 Propagation data required for the design systems in the land mobile-satellite service

- P.682 Propagation data required for the design of Earth-space aeronautical mobile telecommunication systems
- P.683 Sky-wave field strength prediction method for propagation to aircraft at about 500 kHz  
Note - Suppressed on 20/10/95 (RA-95)
- P.684 Prediction of field strength at frequencies below about 150 kHz
- P.832 World Atlas of Ground Conductivities
- P.833 Attenuation in vegetation
- P.834 Effects of tropospheric refraction on radiowave propagation
- P.835 Reference standard atmospheres
- P.836 Water vapour: surface density and total columnar content
- P.837 Characteristics of precipitation for propagation modelling
- P.838 Specific attenuation model for rain for use in prediction methods
- P.839 Rain height model for prediction methods
- P.840 Attenuation due to clouds and fog
- P.841 Conversion of annual statistics to worst-month statistics
- P.842 Computation of reliability and compatibility of HF radio systems
- P.843 Communication by meteor-burst propagation
- P.844 Ionospheric factors affecting frequency sharing in the VHF and UHF bands (30 MHz-3 GHz)
- P.845 HF field-strength measurement
- P.846 Measurements of ionospheric and related characteristics
- P.1057 Probability distributions relevant to radiowave propagation modelling
- P.1058 Digital topographic databases for propagation studies
- P.1059 Method for predicting sky-wave field strengths in the frequency range 1605 to 1705 kHz  
Note - Suppressed on 20/10/95 (RA-95)
- P.1060 Propagation factors affecting frequency sharing in HF terrestrial systems
- P.1144 Guide to the application of the propagation methods of Radiocommunication Study Group 3
- P.1145 Propagation data for the terrestrial land mobile service in the VHF and UHF bands  
Note - Suppressed

- P.1146 The prediction of field strength for land mobile and terrestrial broadcasting services in the frequency range from 1 to 3 GHz  
Note - Suppressed on 22/10/01 (CACE/233)
- P.1147 Prediction of sky-wave field strength at frequencies between about 150 and 1 700 kHz
- P.1148 Standardized procedure for comparing predicted and observed HF sky-wave signal intensities and the presentation of such comparisons
- P.1238 Propagation data and prediction methods for the planning of indoor radiocommunication systems and radio local area networks in the frequency range 300 MHz to 450 GHz
- P.1239 ITU-R reference ionospheric characteristics
- P.1240 ITU-R methods of basic MUF, operational MUF and ray-path prediction
- P.1321 Propagation factors affecting systems using digital modulation techniques at LF and MF
- P.1322 Radiometric estimation of atmospheric attenuation  
Suppressed on 29/07/2015 (CACE/745)
- P.1406 Propagation effects relating to terrestrial land mobile and broadcasting services in the VHF and UHF bands
- P.1407 Multipath propagation and parameterization of its characteristics
- P.1409 Propagation data and prediction methods for systems using high altitude platform stations and other elevated stations in the stratosphere at frequencies greater than about 0.7 GHz
- P.1410 Propagation data and prediction methods required for the design of terrestrial broadband radio access systems operating in a frequency range from 3 to 60 GHz
- P.1411 Propagation data and prediction methods for the planning of short-range outdoor radiocommunication systems and radio local area networks in the frequency range 300 MHz to 100 GHz
- P.1412 Propagation data for the evaluation of coordination between Earth stations working in the bidirectionally allocated frequency bands
- P.1510 Mean surface temperature
- P.1511 Topography for Earth-space propagation modelling
- P.1546 Method for point-to-area predictions for terrestrial services in the frequency range 30 MHz to 4 000 MHz
- P.1621 Propagation data required for the design of Earth-space systems operating between 20 THz and 375 THz
- P.1622 Prediction methods required for the design of Earth-space systems operating between 20 THz and 375 THz

- P.1623 Prediction method of fade dynamics on Earth-space paths
- P.1791 Propagation prediction methods for assessment of the impact of ultra-wideband devices
- P.1812 A path-specific propagation prediction method for point-to-area terrestrial services in the frequency range 30 MHz to 6 000 MHz
- P.1814 Prediction methods required for the design of terrestrial free-space optical links
- P.1815 Differential rain attenuation
- P.1816 The prediction of the time and the spatial profile for broadband land mobile services using UHF and SHF bands
- P.1817 Propagation data required for the design of terrestrial free-space optical links
- P.1853 Time series synthesis of tropospheric impairments
- P.2001 A general purpose wide-range terrestrial propagation model in the frequency range 30 MHz to 50 GHz
- P.2040 Effects of building materials and structures on radiowave propagation above about 100 MHz
- P.2041 Prediction of path attenuation on links between an airborne platform and Space and between an airborne platform and the surface of the Earth
- P.2108 Prediction of clutter loss
- P.2109 Prediction of building entry loss
- P.2145 Digital maps related to the calculation of gaseous attenuation and related effects
- P.2146 Sea surface bistatic scattering
- P.2147 Acquisition, presentation, analysis and use of digital products in studies of radiowave propagation
- P.2148 Digital maps related to surface wind speed statistics